EIC SEARCH RESULTS

Serial No. 10/718,804 – Demineralized bone implants

Searcher: Ethel Leslie Date: March 19, 2009

Inventor Search

Search Strategy

```
Items
               Description
S1
        1561 S AU=(BOYER M? OR BOYER, M?)
S2
        5175 S AU=(PAUL D? OR PAUL, D?)
         112 S AU=(ANGELUCCI C? OR ANGELUCCI, C?)
S3
S4
          23 S S1 AND S2 AND S3
S5
          15 S S4 FROM 350, 347
              S S4 NOT S5
S6
           8
S7
           6
                RD (unique items)
S8
          98
                S S1:S3 AND ((BONE? ? OR OSSEOUS? OR OSTEO?) (5N) (IMPLANT?
OR BLOCK? ? OR PELLET? OR PROSTHES? OR GRAFT? OR AUTOGRAFT? OR TRANSPLANT? OR
XENOGRAFT? OR ALLOGRAFT? OR HOMOGRAFT?))
               S S8 NOT S4
          82
              S S9 FROM 350, 347
S10
          10
          72
S11
              S S9 NOT S10
S12
           48
                RD (unique items)
[File 350] Derwent WPIX 1963-2008/UD=200915
(c) 2009 Thomson Reuters. All rights reserved.
[File 347] JAPIO Dec 1976-2008/Oct(Updated 090220)
(c) 2009 JPO & JAPIO. All rights reserved.
[File 155] MEDLINE (R) 1950-2009/Mar 16
(c) format only 2009 Dialog. All rights reserved.
[File 73] EMBASE 1974-2009/Mar 17
(c) 2009 Elsevier B.V. All rights reserved.
[File 5] Biosis Previews(R) 1926-2009/Mar W3
(c) 2009 The Thomson Corporation. All rights reserved.
[File 8] Ei Compendex (R) 1884-2009/Mar W1
(c) 2009 Elsevier Eng. Info. Inc. All rights reserved.
[File 35] Dissertation Abs Online 1861-2009/Feb
(c) 2009 ProQuest Info&Learning. All rights reserved.
[File 65] Inside Conferences 1993-2009/Mar 18
(c) 2009 BLDSC all rts. reserv. All rights reserved.
```

Search Results

```
5/25/1 (Item 1 from file: 350) Links
Fulltext available through: Order File History
Derwent WPIX
(c) 2009 Thomson Reuters. All rights reserved.

0018591463 & & Drawing available
WPI Acc no: 2009-A89861/200904
```

Related WPI Acc No: 2003-110482; 2002-740210; 2002-740212; 2002-740213; 2004-419519; 2004-728388; 2005-404640

Implant for treating bone fractures and bone defects, comprises unitary section of cortical bone having mineralized first portion and partially demineralized second portion

Patent Assignee: ANGELUCCI C M (ANGE-I); BOYER M L (BOYE-I); PAUL D C (PAUL-I)

Inventor: ANGELUCCI C M; BOYER M L; PAUL D C

Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Type
US 20090005882	A1	20090101	200904	В

US 20090005882

Local Applications (no., kind, date): US 2001271745 P 20010228; US 2001927333 A 20010813; US 200545404 A 20050131; US 2008206435 A 20080908 Priority Applications (no., kind, date): US 2001271745 P 20010228; US 2001927333 A 20010813; US 200545404 A 20050131; US 2008206435 A 20080908

Alerting Abstract US A1

NOVELTY - **Implant** comprises unitary section of **cortical bone** having mineralized first portion and at least partially demineralized second portion, where mineralized portion includes plurality of slits to facilitate bending of unitary section.

USE - The **implant**, preferably allo**graft implant** is useful for **treat**ing **bone** fractures caused due to **bone** loss or injuries, and **bone** defects caused due to trauma or infection.

5/25/2 (Item 2 from file: 350) Links

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0015056611 & & Drawing available

WPI Acc no: 2005-404640/200541

Related WPI Acc No: 2002-740210; 2002-740212; 2002-740213; 2003-110482; 2004-419519; 2004-728388; 2009-A89861

Demineralized bone-derived sheet implant use for treating bone fractures and defects, has bone strips with bone grain orientations that are disposed transverse to the grain orientations of other bone strips

Patent Assignee: SYNTHES (SYNT-N)

Inventor: ANGELUCCI C M; BOYER M L; PAUL D C

Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Туре
US 20050131548	A1	20050616	200541	В

US 20050131548

Local Applications (no., kind, date): US 2001271745 P 20010228; US 2001927333 A 20010813; US 200545404 A 20050131

Priority Applications (no., kind, date): US 2001271745 P 20010228; US 2001927333 A 20010813; US 200545404 A 20050131

Alerting Abstract US A1

NOVELTY - The demineralized **bone**-derived **sheet implant** (70) includes strips (72,74) of **bone** each having a **bone** grain orientation. The **bone** grain orientation orientation orientation

of the other strips. The strips are interwoven. Each strip is selected from a group consisting of mineralized **bone**, demineralized **bone**, partially demineralized **bone**.

USE - Use for treating bone fractures and defects.

ADVANTAGE - Provides **sheet implant** formed from partially or fully demineralized **cancellous bone**. Provides an **implant** that has been selectively masked during demineralization so that portions of the **bone** are at least partially demineralized while other portions substantially remain in the mineralized state.

DESCRIPTION OF DRAWINGS - The figure shows the woven **bone sheet implant**. 70 Demineralized **bone**-derived **sheet implant** 72,74 Strips

5/25/4 (Item 4 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0014546432 & & Drawing available

WPI Acc no: 2004-728388/200471

Related WPI Acc No: 2002-740210; 2002-740212; 2002-740213; 2003-110482; 2004-419519; 2005-404640; 2009-A89861

Allograft implant for maintaining distance between cut spinal bones in spinal column during laminoplasty procedure, has bone flap provided to plate ends and fixable to spinal bones by fasteners to ensure distance between bones

Patent Assignee: ANGELUCCI C M (ANGE-I); BOYER M L (BOYE-I); PAUL D C (PAUL-I); RYAN C J (RYAN-I); SINHA A (SINH-I); WALTHER M (WALT-I)

Inventor: ANGELUCCI C M; BOYER M L; PAUL D C; RYAN C J; SINHA A; WALTHER M
Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Type
US 20040210222	A1	1211114 1 112 1	200471	В

US 20040210222

Local Applications (no., kind, date): US 2001271745 P 20010228; US 2001942137 A 20010829; US 2004844249 A 20040512

Priority Applications (no., kind, date): US 2001271745 P 20010228; US 2001942137 A 20010829; US 2004844249 A 20040512

Alerting Abstract US A1

NOVELTY - The allo**graft implant** (30) has a length that is **size**d to span between the spinal **bone**s of a vertebra. **Bone** flaps (31A,31B) are provided to the **implant** ends (32A,32B) to engage with the spinal **bone**s. Each **bone** flap is provided with a fastener hole (36A,36B) for receiving a fastener that fixes each flap to the respective **bone** in order to maintain a predetermined distance between the **bone**s.

DESCRIPTION - An INDEPENDENT CLAIM is also included for a distance maintaining procedure between spinal **bone**s of spinal column using **implant**. USE - For maintaining distance between cut spinal **bone**s in spinal column during laminoplasty procedure.

ADVANTAGE - Pressure on spinal cord caused by impinging of vertebral **bone** can be eliminated through expansion of spinal canal by using **implant** to maintain distance between vertebral **bone**s. Provides excellent dimension, strength and retention capability to enable simple fitting and installation to patient's **bone** in spinal column. Enables securing **implant** to cut lamina segments without requiring use of a separate plate.

 ${\tt DESCRIPTION\ OF\ DRAWINGS\ -\ The\ figure\ shows\ the\ perspective\ view\ of\ unilateral}$

implant incorporating demineralized bone flaps.

30 Allograft implant

31A,31B Bone flaps

32A, 32B Implant ends

36 **Implant** outer surface

36A,36B Fastener hole

5/25/5 (Item 5 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX *** CURRENT APPLICATION ***

(c) 2009 Thomson Reuters. All rights reserved.

0014233573 & & Drawing available

WPI Acc no: 2004-419519/200439

Related WPI Acc No: 2002-740210; 2002-740212; 2002-740213; 2003-110482; 2004-728388; 2005-404640; 2009-A89861

Implant providing method for producing bone implant made from partially demineralized or demineralized bone, involves demineralizing block of cancellous bone having first geometry, before block is wet and compressed to second geometry

Patent Assignee: SYNTHES USA (SYNT-N)

Inventor: ANGELUCCI C M; BOYER M L; PAUL D C

Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Туре
US 20040107003	A1	20040603	200439	В

US 20040107003

Local Applications (no., kind, date): US 2001271745 P 20010228; US 2001927335 A 20010813; US 2003718804 A 20031124

Priority Applications (no., kind, date): US 2001271745 P 20010228; US 2001927335 A 20010813; US 2003718804 A 20031124

Alerting Abstract US A1

NOVELTY - The method involves demineralizing a **block** of **cancellous bone** (40) having a first geometry, before the **block** is **wet**. The **wet block** is **compress**ed from a first geometry to a second geometry.

USE - For **produc**ing **bone implant** made from partially demineralized or demineralized **bone** and used to **treat bone** fractures and defects.

ADVANTAGE - Ensures reliable formation of **bone** from partially demineralized or demineralized **bone**.

DESCRIPTION OF DRAWINGS - The figure shows the isometric view of the **cortical** shell.

- 40 Block of cancellous bone
- 42 **Pellet**
- 44 Cylinder
- 46 Cage
- 48 Perforations

5/25/8 (Item 8 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0013215758 & & Drawing available WPI Acc no: 2003-300336/200329

XRPX Acc No: N2003-239074

Implant for spinal column, has graft engaging portion which is configured to retain allograft when allograft contacts graft engaging portion

Patent Assignee: ANGELUCCI C M (ANGE-I); BOYER M L (BOYE-I); PAUL D C (PAUL-I); RYAN C J (RYAN-I); SINHA A (SINH-I); SYNTHES USA (SYNT-N); WALTER M (WALT-I)

Inventor: ANGELUCCI C; ANGELUCCI C M; BOYER M; BOYER M L; PAUL D; PAUL D C; RYAN C; RYAN C J; SINHA A; WALTER M; WALTHER M; ANGELUCCI M; BOYER L; PAUL C; RYAN J

Patent Family (9 patents, 26 & countries)

Patent Number	Kind	Date	Update	Туре
US 20030045936	A1	20030306	200329	В
WO 2003020141	A1	20030313	200341	E
US 6635087	В2	20031021	200370	E
EP 1420708	A1	20040526	200435	E
EP 1420708	В1	20060621	200643	E
DE 60212648	E	20060803	200654	E
EP 1698294	A1	20060906	200659	E
ES 2266543	Т3	20070301	200719	E
DE 60212648	T2	20070621	200743	E

US 20030045936

Local Applications (no., kind, date): US 2001942335 A 20010829; WO 2002US27139 A 20020826; US 2001942335 A 20010829; EP 2002753537 A 20020826; WO 2002US27139 A 20020826; EP 2002753537 A 20020826; WO 2002US27139 A 20020826; DE 60212648 A 20020826; EP 2002753537 A 20020826; WO 2002US27139 A 20020826; EP 2002753537 A 20020826; EP 2002753537 A 20020826; EP 2002753537 A 20020826; DE 60212648 A 20020826; EP 2002753537 A 20020826; WO 2002US27139 A 20020826

Priority Applications (no., kind, date): US 2001942335 A 20010829

Alerting Abstract US A1

NOVELTY - A portion made from non-allo**graft** material has first and second **bone** engaging portions, and an allo**graft** engaging portion. The **graft** engaging portion is configured to retain the allo**graft** when the allo**graft** contacts the **graft** engaging portion.

DESCRIPTION - An INDEPENDENT CLAIM is also included for a method for providing a desired distance between first and second cut bone ends of the spine.

USE - For spinal column.

ADVANTAGE - Can expand the spinal canal to eliminate pressure on the spinal cord caused by an impinging vertebral **bone**. Provides excellent dimensional, strength and retention capability, and enhance fusion with patient's own **bone**, easy to select, fit and install which provide excellent compatibility with post operative imaging.

DESCRIPTION OF DRAWINGS - The figure is the perspective view of an **implant** for unilateral laminoplasty procedure.

5/25/11 (Item 11 from file: 350) <u>Links</u>
Fulltext available through: <u>Order File History</u>
Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0012880926 & & Drawing available WPI Acc no: 2002-740213/200280

Related WPI Acc No: 2002-740210; 2002-740212; 2003-110482; 2004-419519; 2004-728388; 2005-404640; 2009-A89861

Forming method for demineralized bone implant, involves demineralizing cancellous bone section, then compressing bone section into smaller geometry and drying same bone section

Patent Assignee: ANGELUCCI C M (ANGE-I); BOYER M L (BOYE-I); PAUL D C (PAUL-I); SYNTHES (SYNT-N); SYNTHES USA (SYNT-N); SYNTHES GMBH (SYNT-N)

Inventor: ANGELUCCI C M; BOYER M L; PAUL D C; ANGELUCCI C ; BOYER M; PAUL D

Patent Family (8 patents, 95 & countries)

Patent Number	Kind	Date	Update	Туре
US 20020120347	A1	20020829	200280	В
WO 2002069818	A2	20020912	200280	E
US 6652593	B2	20031125	200378	E
AU 2001283368	A1	20020919	200433	E
EP 1424948	A2	20040609	200438	E
AU 2001283368	A8	20051027	200624	E
EP 1424948	B1	20081210	200904	E
DE 60136971	E	20090122	200909	E

US 20020120347

Local Applications (no., kind, date): US 2001271745 P 20010228; US 2001927335 A 20010813; WO 2001US25455 A 20010814; US 2001927335 A 20010813; AU 2001283368 A 20010814; EP 2001962169 A 20010814; WO 2001US25455 A 20010814; AU 2001283368 A 20010814; EP 2001962169 A 20010814; WO 2001US25455 A 20010814; DE 60136971 A 20010814; EP 2001962169 A 20010814; WO 2001US25455 A 20010814

Priority Applications (no., kind, date): US 2001271745 P 20010228; US 2001271745 P 20010228; US 2001927335 A 20010813; US 2001927333 A 20010813; US 2001927334 A 20010813; US 2001927335 A 20010813

Alerting Abstract US A1

NOVELTY - The method involves demineralizing a **cancellous bone** section of a predetermined geometry. The **bone** section is obtained from e.g. femur, tibia, humerus, fibula, ulna. The demineralized **bone** section is then **compress**ed to a smaller geometry and then **drie**d. The **bone** section is then filled into a space, a **bony** defect or a cavity.

DESCRIPTION - INDEPENDENT CLAIMS are included for the following:

a method of maintaining distance between vertebral bodies; a method of replacing nucleus of a vertebral disc; and an **implant**.

USE - For forming demineralized **bone implant** for filling voids, **bone** defects or other regions e.g. cavities, within spinal cages, as well as **bony** defects caused by removal of **bone** screws or diseased **bone**. Also used as e.g. **cortical** shell, burr hole cover in cranial region of skull.

ADVANTAGE - Enables demineralized **cancellous bone** to be used as **soft** substance for enhancing anatomical areas during e.g. plastic surgery, face lifts, chin augmentations, cheek enhancements, eye brow lifts, or suited for filling defect regions caused by disease, congenital conditions or surgical procedure. Minimizes degree of brittleness of **bone**. Makes **implant** suitable in **treat**ment of brain problems e.g. tumors, aneurysm, blood clots, head injuries, abscesses, as well as medical procedures e.g. laminoplasty, nucleus replacements, disc or ligament replacement.

DESCRIPTION OF DRAWINGS - The figure shows the perspective view of a **cortical** shell.

5/25/12 (Item 12 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0012880925 & & Drawing available

WPI Acc no: 2002-740212/200280

Related WPI Acc No: 2002-740210; 2002-740213; 2003-110482; 2004-419519; 2004-

728388; 2005-404640; 2009-A89861

Bone sheet for demineralized bone-derived implant has partially demineralized field surrounding at least one mineralized region

Patent Assignee: ANGELUCCI C M (ANGE-I); BOYER M L (BOYE-I); PAUL D C (PAUL-I); SYNTHES USA (SYNT-N)

Inventor: ANGELUCCI C M; BOYER M L; PAUL D C

Patent Family (2 patents, 1 & countries)

Patent Number	Kind	Date	Update	Туре
US 20020120346	A1	20020829	200280	В
US 6855169	В2	20050215	200513	E

US 20020120346

Local Applications (no., kind, date): US 2001271745 P 20010228; US 2001927333 A 20010813; US 2001927333 A 20010813

Priority Applications (no., kind, date): US 2001271745 P 20010228; US 2001927333 A 20010813; US 2001927333 A 20010813

Alerting Abstract US A1

NOVELTY - The **bone sheet** includes a partially demineralized field surrounding at least one mineralized region.

 ${\tt DESCRIPTION-An\ INDEPENDENT\ CLAIM\ is\ also\ included\ for\ a\ flexible\ bone\ sheet} \\ {\tt manufacturing\ method.}$

USE - For demineralized bone-derived implant.

ADVANTAGE - Enables partial demineralization of portions of **bone**, while other **bone** portions are remain in mineralized state. Enables solidifying

demineralized **cortical** fibers to desired geometry to portions of **bone** with significant strength.

DESCRIPTION OF DRAWINGS - The figure shows the bendable demineralized **bone**-derived **implant**.

5/25/13 (Item 13 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0012880923 & & *Drawing available*

WPI Acc no: 2002-740210/200280

Related WPI Acc No: 2002-740212; 2002-740213; 2003-110482; 2004-419519; 2004-728388; 2005-404640; 2009-A89861

Cranial void filler includes lower, partially demineralized cortical bone section which is adapted and configured to contact walls of cranial void

Patent Assignee: ANGELUCCI C M (ANGE-I); BOYER M L (BOYE-I); PAUL D C (PAUL-I); SYNTHES USA (SYNT-N)

Inventor: ANGELUCCI C M; BOYER M L; PAUL D C

Patent Family (2 patents, 1 & countries)

Patent Number	Kind	Date	Update	Type
US 20020120338	A1	20020829	200280	В
US 6776800	B2	20040817	200454	E

US 20020120338

Local Applications (no., kind, date): US 2001271745 P 20010228; US 2001927334 A 20010813; US 2001927334 A 20010813

Priority Applications (no., kind, date): US 2001271745 P 20010228; US 2001927334 A 20010813; US 2001927334 A 20010813

Alerting Abstract US A1

NOVELTY - The cranial void filler includes a lower, partially demineralized cortical bone section which is adapted and configured to contact walls of a cranial void. The cranial void filler also includes an upper mineralized cortical bone section.

DESCRIPTION - INDEPENDENT CLAIMS are also included for the following:

a plate;

an implant;

and a method for forming an implant.

USE - Used for filling voids, **bone** defects, or other regions such as the cavities inside spinal cages. Used for enhancing anatomical areas. Used in the replacement of **bone** at the site of a previous excision in order to reestablish support and protection of the spinal cord.

ADVANTAGE - Enables **produc**tion of larger **implant**s since the strength of the **implant**s is improved. Enables reliably filling in the cranial void since filler has partially demineralized **cortical bone** section which is **soft**er than other sections of the cranial void filler.

DESCRIPTION OF DRAWINGS - The figure shows a bendable implant.

5/25/14 (Item 14 from file: 350) Links

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0010959389 & & Drawing available

WPI Acc no: 2001-582625/200165

Related WPI Acc No: 2001-582622; 2001-582623; 1999-469223; 2000-586816; 2002-

267759

XRPX Acc No: N2001-434065

Skeletal reconstruction cage has first end cap which is coupled to first end of central body and has second end cap which is coupled to second end of central body

Patent Assignee: ANGELUCCI C M (ANGE-I); BOYER M L (BOYE-I); HIGGINS T B (HIGG-I); PAUL D C (PAUL-I); SYNTHES AG (SYNT-N); SYNTHES USA (SYNT-N)

Inventor: ANGELUCCI C M; BOYER M L; HIGGINS T B; PAUL D C

Patent Family (8 patents, 94 & countries)

Patent Number	Kind	Date	Update	Type
WO 2001070139	A2	20010927	200165	В
US 20010056302	A1	20011227	200206	E
AU 200149367	A	20011003	200210	E
EP 1265557	A2	20021218	200301	E
US 6660038	B2	20031209	200381	E
US 20040181283	A1	20040916	200461	E

AU 2001249367	A8	20051013	200611	E
US 7014659	В2	20060321	200621	E

WO 2001070139

Local Applications (no., kind, date): WO 2001US9269 A 20010322; US 2000191099 P 20000322; US 2001814215 A 20010322; AU 200149367 A 20010322; EP 2001922581 A 20010322; WO 2001US9269 A 20010322; US 2000191099 P 20000322; US 2001814215 A 20010322; US 2000191099 P 20000322; US 2003730011 A 20031209; AU 2001249367 A 20010322; US 2000191099 P 20000322; US 2001814215 A 20010322; US 2001814215 A 20010322; US 2003730011 A 20031209 Priority Applications (no., kind, date): US 2000191099 P 20000322; US 2001814215 A 20010322; US 2003730011 A 20031209

Alerting Abstract WO A2

NOVELTY - A first end cap is coupled to the first end of a central body. A second end cap is coupled to the second end of the central body. USE - Used for filling vacancies in **bone tissue**.

ADVANTAGE - Permits wide range of angles, heights and configurations to be accommodated so that particular anatomical defect may be spanned. DESCRIPTION OF DRAWINGS - The figure shows the side view and the top view of a central shaft.

7/7/2 (Item 2 from file: 5) Links
Biosis Previews(R)

(c) 2009 The Thomson Corporation. All rights reserved.

18650639 Biosis No.: 200510345139 Demineralized bone-derived implants

Author: Boyer, Michael L; Paul David C; Angelucci Christopher M

Author Address: Paoli, PA USA**USA

Journal: Official Gazette of the United States Patent and Trademark Office

Patents FEB 15 2005 2005

ISSN: 0098-1133

Document Type: Patent
Record Type: Abstract
Language: English

Abstract: Selectively demineralized bone-derived implants are provided. In one embodiment, a bone sheet for implantation includes a demineralized field surrounding mineralized regions. In another embodiment, a bone defect filler includes a demineralized cancellous bone section in a first geometry. The first geometry is compressible and dryable to a second geometry smaller than the first geometry, and the second geometry is expandable and rehydratable to a third geometry larger than the second geometry.

7/7/3 (Item 3 from file: 5) <u>Links</u>
Biosis Previews(R)
(c) 2009 The Thomson Corporation. All rights reserved.
18011174 Biosis No.: 200400381963
Implants formed with demineralized bone

Author: Boyer Michael L (Reprint); Paul David C; Angelucci Christopher M Journal: Official Gazette of the United States Patent and Trademark Office Patents 1285 (3): Aug. 17, 2004 2004

Medium: e-file

ISSN: 0098-1133 _(ISSN print)

Document Type: Patent Record Type: Abstract Language: English

Abstract: Selectively partially and demineralized bone-derived implants, their methods of preparation and use are provided. In one embodiment, a cranial void filler preferably having a T-shape formed of an upper mineralized cortical bone section and at least a partially demineralized lower section adapted to fill a cranial void is disclosed. In another embodiment, a plate preferably having a dog-bone-shape having mineralized and at least partially demineralized sections is disclosed. In a further embodiment, a unitary cord having a first mineralized section with a plurality of slits to provide flexibility and a second at least partially demineralized section is described. Also disclosed is an implant for laminoplasty having at least a partially demineralized section and a mineralized section. A method of forming an implant of demineralized fibers also is disclosed.

7/7/4 (Item 4 from file: 5) <u>Links</u>

Biosis Previews(R)

(c) 2009 The Thomson Corporation. All rights reserved.

17973962 **Biosis No.:** 200400344751

Plugs for filling bony defects

Author: Boyer Michael L (Reprint); Paul David C; Higgins Thomas B; Angelucci

Christopher M; Messerli Dominique D; Kobayashi Kenneth I

Author Address: West Chester, PA, USA**USA

Journal: Official Gazette of the United States Patent and Trademark Office

Patents 1284 (4): July 27, 2004 2004

Medium: e-file

ISSN: 0098-1133 _(ISSN print)

Document Type: Patent Record Type: Abstract Language: English

Abstract: The present invention relates to **plug**s for filling vacancies in **bone tissue.** The **plug**s include a body and at least one end cap that are coupled together and may be formed from **bone.** The body of the **plug** may be a sleeve, and the **plug** may further include an insert configured and dimensioned to be received in the sleeve.

7/7/5 (Item 5 from file: 5) **Links**

Biosis Previews(R)

(c) 2009 The Thomson Corporation. All rights reserved.

17660061 **Biosis No.:** 200400030818

Demineralized bone implants

Author: Boyer Michael L (Reprint); Paul David C; Angelucci Christopher M

Author Address: Schwenksville, PA, USA**USA

Journal: Official Gazette of the United States Patent and Trademark Office

Patents 1276 (4): Nov. 25, 2003 2003

Medium: e-file

ISSN: 0098-1133 _(ISSN print)

Document Type: Patent

Record Type: Abstract Language: English

Abstract: Selectively demineralized bone-derived implants are provided. In one embodiment, a bone sheet for implantation includes a demineralized field surrounding mineralized regions. In another embodiment, a bone defect filler includes a demineralized cancellous bone section in a first geometry. The first geometry is compressible and dryable to a second geometry smaller than the first geometry, and the second geometry is expandable and rehydratable to a third geometry larger than the second geometry.

10/25/1 (Item 1 from file: 350)

Fulltext available through:

Derwent WPIX

Links
Order File History

(c) 2009 Thomson Reuters. All rights reserved.

0015353164 & & Drawing available WPI Acc no: 2005-703425/200572 XRPX Acc No: N2005-577099

Multi-piece implant for intervertebral fusion, includes cortical bone segments formed with male and female locking surfaces, connected by inserting locking pins into holes extending through cortical bone segments

Patent Assignee: ANGELUCCI C M (ANGE-I); BOYER M L (BOYE-I); DELURIO R J (DELU-I); GOODWIN R D (GOOD-I); MESSERLI D (MESS-I); MYER J (MYER-I); RANDALL B L (RAND-I); SYNTHES (SYNT-N); SYNTHES USA (SYNT-N); SYNTHES USA LLC (SYNT-N)

Inventor: ANGELUCCI C; ANGELUCCI C M; BOYER M; BOYER M L; DELURIO R; DELURIO R J; GOODWIN R; GOODWIN R D; MESSERLI D; MYER J; RANDALL B; RANDALL B L; ANGELUCCI C H

Patent Family (11 patents, 108 & countries)

Patent Number	Kind	Date	Update	Type
WO 2005097004	A2	20051020	200572	В
US 20050240267	A1	20051027	200572	E
EP 1732480	A2	20061220	200702	E
AU 2005231346	A1	20051020	200720	E
KR 2006130768	A	20061219	200742	E
BR 200509185	A	20070918	200763	E
IN 200603927	P4	20070615	200765	E
JP 2007530177	W	20071101	200780	E
CN 101027015	A	20070829	200806	E
ZA 200608184	A	20080625	200848	E
US 7491237	В2	20090217	200914	E

WO 2005097004

Local Applications (no., kind, date): WO 2005US10255 A 20050328; US 2004556860 P 20040326; US 200593111 A 20050328; EP 2005731330 A 20050328; WO 2005US10255 A 20050328; AU 2005231346 A 20050328; WO 2005US10255 A 20050328; KR 2006722282 A 20061026; BR 20059185 A 20050328; WO 2005US10255 A 20050328; WO 2005US10255 A 20050328; IN 2006CN3927 A 20061026; WO 2005US10255 A 20050328; JP 2007505258 A 20050328; CN 200580016242 A 20050328; WO 2005US10255 A 20050328; ZA 20068184 A 20050328; US 2004556860 P 20040326; US 200593111 A 20050328

Priority Applications (no., kind, date): US 2004556860 P 20040326; US 2004556860 P 20040326; US 200593111 A 20050328

Alerting Abstract WO A2

NOVELTY - Each **implant** (10) has **cortical bone** segments (30,40,50) formed with male and female locking surfaces. The locking pins are inserted through the holes extending through the **cortical bone** segments so as to connect the **cortical bone** segments for forming the multi-piece **implant**.

DESCRIPTION - INDEPENDENT CLAIMS are also included for the following:

multi-piece intervertebral **implant manufactur**ing method; and intervertebral **implant** kit.

USE - For intervertebral fusion for **treat**ment of back pain caused by **compress**ion of spinal cord nerve roots, degenerative vertebral disc diseases and trauma.

ADVANTAGE - Ensures reliable locking of the **cortical bone** segments, without separation of the **bone** segments during **implantation** within the patient. DESCRIPTION OF DRAWINGS - The figure shows a perspective view of the intervertebral **implant**.

- 10 intervertebral implant
- 14 upper surface
- 16 lower surfaces
- 24 pyramid **shape**d teeth
- 30,40,50 **cortical bone** segments

10/25/2 (Item 2 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0014848679 & & Drawing available WPI Acc no: 2005-196381/200520 XRPX Acc No: N2005-162131

Intervertebral implant used for vertebrae fusion surgery, has two portions which are connected with dovetail joint and formed superior and inferior surfaces each having several teeth

Patent Assignee: ANGELUCCI C H (ANGE-I); ANGELUCCI C M (ANGE-I); BOYER M L (BOYE-I); BOYER M L I (BOYE-I); MESSERLI D (MESS-I); MYER J (MYER-I); SYNTHES GMBH (SYNT-N); SYNTHES USA (SYNT-N)

Inventor: ANGELUCCI C H; BOYER M L; MESSERLI D; MYER J; ANGELUCCI C M; BOYER
M L I

Patent Family (12 patents, 107 & countries)

Patent Number	Kind	Date	Update	Туре
WO 2005020861	A1	20050310	200520	В
US 20050113918	A1	20050526	200535	E
EP 1670396	A1	20060621	200643	E
BR 200414078	A	20061024	200671	E
AU 2004268673	A1	20050310	200674	E
JP 2007503924	W	20070301	200718	E
US 7226482	В2	20070605	200737	NCE
CN 1901853	A	20070124	200740	E
US 20070208424	A1	20070906	200760	E
ZA 200602137	A	20070829	200772	E
IN 200601112	P4	20070817	200780	E
KR 2007097290	A	20071004	200819	E

Local Applications (no., kind, date): WO 2004US28544 A 20040902; US 2003499926 P 20030902; US 2004931788 A 20040901; EP 2004782938 A 20040902; WO 2004US28544 A 20040902; BR 200414078 A 20040902; WO 2004US28544 A 20040902; AU 2004268673 A 20040902; WO 2004US28544 A 20040902; JP 2006525432 A 20040902; US 2004931788 A 20040901; CN 200480032221 A 20040902; US 2003499926 P 20030902; US 2004931788 A 20040901; US 2007745343 A 20070507; ZA 20062137 A 20040902; WO 2004US28544 A 20040902; IN 2006CN1112 A 20060331; WO 2004US28544 A 20040902; KR 2006704363 A 20060302

Priority Applications (no., kind, date): US 2003499926 P 20030902; US 2004931788 A 20040901; US 2007745343 A 20070507

Alerting Abstract WO A1

NOVELTY - Two **implant** portions are connected with a dovetail joint and formed superior and inferior surfaces (14,16) each having several teeth.

DESCRIPTION - An INDEPENDENT CLAIM is included for a **manufactur**ing method of

an intervertebral implant.
USE - Used for vertebrae fusion surgery.

ADVANTAGE - Ensures optimal fit of **implant** between vertebrae and promotes fusion of vertebrae with the **implant** without excessive contouring of the surfaces of **implant**. Maximizes **bone** growth. Prevents short-term slippage of **implant** until the **implant** is fused.

DESCRIPTION OF DRAWINGS - The figure is the perspective view of an **implant**. 6 Anterior end

10 Implant

14,16 Superior and inferior surfaces

18 Exterior surface

10/25/6 (Item 6 from file: 350) Links

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0010959387 & & Drawing available WPI Acc no: 2001-582623/200165

Related WPI Acc No: 1999-469223; 2000-586816; 2001-582622; 2001-582625; 2002-

267759

XRPX Acc No: N2001-434063

Implant used for orthopedic operation, has inner sheath and outer sheaths made from different bones, such that exterior surface of outer sheath contact interior surfaces of other outer sheaths

Patent Assignee: BOYER M L (BOYE-I); HIGGINS T B (HIGG-I); PAUL D C (PAUL-I); SYNTHES AG (SYNT-N); SYNTHES USA (SYNT-N)

Inventor: BOYER M; BOYER M L; HIGGINS T; HIGGINS T B; PAUL D; PAUL D C; BOYER
L; HIGGINS B; PAUL C

Patent Family (14 patents, 94 & countries)

Patent Number	Kind	Date	Update	Type
WO 2001070137	A2	20010927	200165	В
US 20010039456	A1	20011108	200171	E
US 20010039458	A1	20011108	200171	E
US 20010041941	A1	20011115	200172	E
AU 200149369	A	20011003	200210	E
EP 1296620	A2	20030402	200325	E
US 6632247	В2	20031014	200368	E
US 20040075192	A1	20040422	200428	E
AU 2001249369	A8	20051006	200610	E

US	7087087	В2	20060808	200652	E
ΕP	1296620	B1	20061108	200674	E
US	20060276907	A1	20061207	200681	E
EP	1296620	В8	20061227	200702	E
DE	60124399	E	20061221	200703	E

WO 2001070137

Local Applications (no., kind, date): WO 2001US9273 A 20010322; US 2000191099 P 20000322; US 2001814114 A 20010322; US 2000191099 P 20000322; US 2001814216 A 20010322; US 2000191099 P 20000322; US 2001814224 A 20010322; AU 200149369 A 20010322; EP 2001922583 A 20010322; WO 2001US9273 A 20010322; US 2000191099 P 20000322; US 2001814216 A 20010322; US 2001814216 A 20010322; US 2001814216 A 20010322; US 2003682996 A 20031014; AU 2001249369 A 20010322; US 20031014; EP 2001922583 A 20010322; WO 2001US9273 A 20010322; US 2003682996 A 20031014; EP 2001922583 A 20010322; WO 2001US9273 A 20010322; US 2000191099 P 20000322; US 2001814224 A 20010322; US 2006505648 A 20060817; EP 2001922583 A 20010322; WO 2001US9273 A 20010322; EP 2001922583 A 20010322; WO 2001US9273 A 20010322; DE 60124399 A 20010322; EP 2001922583 A 20010322; WO 2001US9273 A 20010322

Priority Applications (no., kind, date): US 2000191099 P 20000322; US 2001814114 A 20010322; US 2001814216 A 20010322; US 2001814224 A 20010322; US 2003682996 A 20031014; US 2006505648 A 20060817

Alerting Abstract WO A2

NOVELTY - An **implant** (16) has an inner sheath (18) and at least one outer sheath (17) made from different bones, such that exterior surface of the outer sheath contact the interior surfaces of other outer sheaths.

DESCRIPTION - An INDEPENDENT CLAIM is also included for forming an **implant**.

USE - Used for orthopedic operation.

ADVANTAGE - Offers improved **implant** which ensures efficient utilization of **bone** sections and is formed by integrated **bone** fragments which are interlocked and formed a mechanically effective strong unit.

DESCRIPTION OF DRAWINGS - The figure shows a perspective view of the **bone** portions which are combined to form an **implant**.

- 16 Implant
- 17 Outer sheath
- 18 Inner sheath

10/25/7 (Item 7 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0010273968 & & *Drawing available*

WPI Acc no: 2000-586816/200055

Related WPI Acc No: 1999-469223; 2001-582622; 2001-582623; 2001-582625; 2002-

267759

XRPX Acc No: N2000-434279

Intervertebral allograft spacer for use as an allogenic implant comprises implant with top section joined to the bottom allowing smaller sections of allogenic bone and pin passing through aligned holes

Patent Assignee: EMCH H W (EMCH-I); MUSCULOSKELETAL TRANSPLANT FOUND (MUSC-N); PAUL D C (PAUL-I); SCHENK B (SCHE-I); SYNTHES (SYNT-N); SYNTHES AG (SYNT-N); SYNTHES CHUR AG (SYNT-N); SYNTHES USA (SYNT-N); YACCARINO J A (YACC-I) Inventor: EMCH H; EMCH H W; PAUL D; PAUL D C; SCHENK B; YACCARINO J A; BOYER M L; HIGGINS T B

Patent Fa	amily (12	patents,	21	&	countries))
-----------	---------	----	----------	----	---	-------------	---

Patent Number	Kind	Date	Update	Туре
WO 2000007527	A1	20000217	200055	В
EP 1100417	A1	20010523	200130	E
US 6258125	B1	20010710	200141	E
US 20020062153	A1	20020523	200239	E
US 6554863	В2	20030429	200331	E
EP 1100417	B1	20040407	200425	E
DE 69916280	E	20040513	200434	E
ES 2217796	Т3	20041101	200474	E
CA 2338881	С	20050315	200522	E
DE 69916280	Т2	20050525	200537	E
US 20050261771	A1	20051124	200577	E
US 20060241763	A1	20061026	200671	E

WO 2000007527

Local Applications (no., kind, date): WO 1999EP5541 A 19990730; EP 1999940102 A 19990730; WO 1999EP5541 A 19990730; US 199895209 P 19980803; US 1999363844 A 19990730; US 199895209 P 19980803; US 1999363844 A 19990730; US 2001899086 A 20010706; US 199895209 P 19980803; US 1999363844 A 19990730; US 2001899086 A 20010706; EP 1999940102 A 19990730; WO 1999EP5541 A 19990730; DE 69916280 A 19990730; EP 1999940102 A 19990730; WO 1999EP5541 A 19990730; EP 1999940102 A 19990730; CA 2338881 A 19990730; WO 1999EP5541 A 19990730; DE 69916280 A 19990730; EP 1999940102 A 19990730; WO 1999EP5541 A 19990730; US 199873271 P 19980130; US 199895209 P 19980803; US 199895425 P 19980805; US 1998219439 A 19981223; US 1999363844 A 19990730; US 2001828625 A 20010409; US 2005150584 A 20050609; US 199895209 P 19980803; US 1999363844 A 19990730; US 2001814214 A 20010322; US 2006472211 A 20060620

Priority Applications (no., kind, date): US 199873271 P 19980130; US 199895209 P 19980803; US 199895425 P 19980805; US 1998219439 A 19981223; WO 1999EP5008 A 19990715; US 1999363844 A 19990730; US 2001814214 A 20010322; US 2001828625 A 20010409; US 2001899086 A 20010706; US 2005150584 A 20050609; US 2006472211 A 20060620

Alerting Abstract WO A1

NOVELTY - The intervertebral allo**graft** spacer comprises **implant** (50) with top section (52) joined to the bottom section (54) allowing smaller sections of allogenic **bone** to be used. A top connection surface (56) and bottom connecting surface (58) define the interfaces. To facilitate insertion of the **implant**, the anterior side (26) transitions to superior and inferior surfaces (14,16) with rounded edges (30). A pin (64) passes through aligned holes (66).

USE - For use allogenic intervertebral **implant** conforming with end plates of vertebrae.

ADVANTAGE - The top and bottom surfaces if the **implant** have multiple teeth resisting expulsion and providing initial stability, while the **implant** provides an initial stability to fuse without the stress shielding. DESCRIPTION OF DRAWINGS - Figure of a side view of the **implant**.

- 14,16 Superior and inferior surfaces
- 26 Anterior side
- 50 Implant
- 52 Top section
- 56 Top connection surface
- 58 Connecting surface
- 64 Pin
- 66 Aligned holes

10/25/10 (Item 10 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0009524954 & & Drawing available WPI Acc no: 1999-469223/199939

Related WPI Acc No: 2000-586816; 2001-582622; 2001-582623; 2001-582625; 2002-

267759

XRPX Acc No: N1999-350368

Allogenic intervertebral implant for fusing vertebrae

Patent Assignee: EMCH H (EMCH-I); PAUL D C (PAUL-I); SCHENK B (SCHE-I);

SYNTHES AG (SYNT-N); SYNTHES USA (SYNT-N)

Inventor: BAKER K J; CARVER J L; EMCH H; EMCH H W; PAUL D C; SCHENK B

Patent Family (11 patents, 22 & countries)

Patent Number	Kind	Date	Update	Type
WO 1999038461	A2	19990805	199939	В
EP 1051134	A2	20001115	200059	E
US 6143033	A	20001107	200059	E
US 20010049560	A1	20011206	200203	E
JP 2002501782	M	20020122	200211	E
US RE38614	E	20041005	200466	E
US 20050256574	A1	20051117	200576	E
US 6986788	В2	20060117	200606	E
US 7300465	В2	20071127	200780	E
US 20080046090	A1	20080221	200816	E
US 7347873	В2	20080325	200823	E

WO 1999038461

Local Applications (no., kind, date): WO 1999EP433 A 19990122; EP 1999907405 A 19990122; WO 1999EP433 A 19990122; US 199873271 P 19980130; US 199895425 P 19980805; US 1998219439 A 19981223; US 199873271 P 19980130; US 199895209 P 19980803; US 199895425 P 19980805; US 1998219439 A 19981223; US 1999363844 A 19990730; US 2001828625 A 20010409; WO 1999EP433 A 19990122; JP 2000529197 A 19990122; US 199873271 P 19980130; US 199895209 P 19980803; US 199895425 P 19980805; US 1998219439 A 19981223; US 1999363844 A 19990730; US 2002225282 A 20020822; US 199873271 P 19980130; US 199895209 P 19980803; US 199895425 P 19980805; US 1998219439 A 19981223; US 1999363844 A 19990730; US 2001828625 A 20010409; US 2005150608 A 20050610; US 199873271 P 19980130; US 199895209 P 19980803; US 199895425 P 19980805; US 1998219439 A 19981223; US 1999363844 A 19990730; US 2001828625 A 20010409; US 199873271 P 19980130; US 199895209 P 19980803; US 199895425 P 19980805; US 1998219439 A 19981223; US 1999363844 A 19990730; US 2001828625 A 20010409; US 2005150608 A 20050610; US 199873271 P 19980130; US 199895209 P 19980803; US 199895425 P 19980805; US 1998219439 A 19981223; US 1999363844 A 19990730; US 2001828625 A 20010409; US 2005150608 A 20050610 ; US 2007926569 A 20071029; US 199873271 P 19980130; US 199895209 P 19980803; US 199895425 P 19980805; US 1998219439 A 19981223; US 1999363844 A 19990730; US 2001828625 A 20010409; US 2005150584 A 20050609 Priority Applications (no., kind, date): US 199873271 P 19980130; US 199895209 P 19980803; US 199895425 P 19980805; US 1998219439 A 19981223; US 1999363844 A 19990730; US 2001828625 A 20010409; US 2002225282 A 20020822; US 2005150584 A 20050609; US 2005150608 A 20050610; US 2007926569 A 20071029

NOVELTY - The **implant** (10) comprises an annular **plug** conforming in **size** and **shape** with end plates of vertebrae. The **implant** has either an exterior surface identical to that of the harvest **bone** or an exterior surface machined to have a uniform **shape** such as an oval or a rectangle. The top and bottom surfaces (14,16) of the **implant** have teeth (12) to resist expulsion and provide initial stability. The **implant** is wedge-**shape**d in profile, this helps to restore disc height and the natural curvature of the spine. The surfaces may each have a channel for receiving a surgical instrument.

USE - None given.

ADVANTAGE - Effectively resists expulsion.

DESCRIPTION OF DRAWINGS - The figure shows a top view of the implant.

10 implant

12 teeth

14,16 top and bottom surfaces

12/7/29 (Item 1 from file: 5) Links

Biosis Previews(R)

(c) 2009 The Thomson Corporation. All rights reserved.

0020503251 **Biosis No.:** 200800550190

Intervertebral allograft spacer

Author: Paul David C; Anonymous; Emch Hansjuerg; Schenk Beat

Author Address: Phoenixville, PA USA**USA

Journal: Official Gazette of the United States Patent and Trademark Office

Patents MAR 25 2008 2008

ISSN: 0098-1133

Document Type: Patent **Record Type:** Abstract **Language:** English

Abstract: An allogenic intervertebral implant for fusing vertebrae is disclosed. The implant is a piece of allogenic bone conforming in size and shape with a portion of an end plate of a vertebra. The implant has a wedge-shaped profile to restore disc height and the natural curvature of the spine. The top and bottom surfaces of the implant have a plurality of teeth to resist expulsion and provide initial stability. The implant according to the present invention provides initial stability need for fusion without stress shielding.

12/7/30 (Item 2 from file: 5) Links

Biosis Previews(R)

(c) 2009 The Thomson Corporation. All rights reserved.

0020218640 **Biosis No.:** 200800265579

Intervertebral allograft spacer

Author: Anonymous; Paul David C; Emch Hansjuerg; Schenk Beat

Author Address: Phoenixville, PA USA**USA

Journal: Official Gazette of the United States Patent and Trademark Office

Patents NOV 27 2007 2007

ISSN: 0098-1133

Document Type: Patent **Record Type:** Abstract **Language:** English

Abstract: An allogenic intervertebral implant for fusing vertebrae is

disclosed. The **implant** is a piece of allogenic **bone** conforming in **size** and **shape** with a portion of an end plate of a vertebra. The **implant** has a wedge-**shape**d profile to restore disc height and the natural curvature of the spine. The top and bottom surfaces of the **implant** have a plurality of teeth to resist expulsion and provide initial stability. The **implant** according to the present invention provides initial stability need for fusion without stress shielding.

12/7/31 (Item 3 from file: 5) <u>Links</u>
Biosis Previews(R)
(c) 2009 The Thomson Corporation. All rights reserved.
0019765447 Biosis No.: 200700425188
Multipiece allograft implant

Author: Anonymous; Messerli Dominique; Myer Jacqueline; Boyer Michael L;

Angelucci Christopher H

Author Address: Downington, PA USA**USA

Journal: Official Gazette of the United States Patent and Trademark Office

Patents JUN 5 2007 2007

ISSN: 0098-1133
Document Type: Patent
Record Type: Abstract
Language: English

Abstract: An allogenic implant for use in intervertebral fusion is formed from two parts. The first part, composed of cortical bone, provides mechanical strength to the implant, allowing the proper distance between the vertebrae being treated to be maintained. The second part, composed of cancellous bone, is ductile and promotes the growth of new bone between the vertebrae being treated and the implant, thus fusing the vertebrae to the implant and to each other. The implant is sized and shaped to conform to the space between the vertebrae. Teeth formed on the superior and inferior surfaces of the implant prevent short-term slippage of the implant.

12/7/32 (Item 4 from file: 5) <u>Links</u>
Biosis Previews(R)
(c) 2009 The Thomson Corporation. All rights reserved.
19373943 Biosis No.: 200700033684
Multipiece implants formed of bone material

Author: Anonymous; Boyer Michael L; Paul David C; Higgins Thomas B

Author Address: Paoli, PA 19301 USA**USA

Journal: Official Gazette of the United States Patent and Trademark Office

Patents OCT 3 2006 2006

ISSN: 0098-1133

Document Type: Patent Record Type: Abstract Language: English

Abstract: The present invention relates to an **implant** comprising two or more bone fragments that are combined to form a single unit. Cancellous bone or cortical bone is removed from a source and fashioned into bone components with desirable shapes and sizes. The bone components may be integrated to form **implants** for **implantation** in the body. Bone stock may be formed by combining sections of various bones of the body, and the bone stock may be

further fashioned for use as implants with particular geometries.

12/7/33 (Item 5 from file: 5) Links
Biosis Previews(R)

(c) 2009 The Thomson Corporation. All rights reserved.

19345843 **Biosis No.:** 200700005584

Implants formed of coupled bone

Author: Anonymous; Boyer Michael L; Paul David C; Higgins Thomas B

Author Address: Paoli, PA 19301 USA**USA

Journal: Official Gazette of the United States Patent and Trademark Office

Patents AUG 8 2006 2006

ISSN: 0098-1133

Document Type: Patent **Record Type:** Abstract **Language:** English

Abstract: The present invention relates to an implant comprising two or more bone fragments that are combined to form a single unit. Cancellous bone or cortical bone is removed from a source and fashioned into bone components with desirable shapes and sizes. The bone components may be integrated to form implants for implantation in the body. Bone stock may be formed by combining sections of various bones of the body, and the bone stock may be further fashioned for use as implants with particular geometries.

12/7/34 (Item 6 from file: 5) <u>Links</u>
Biosis Previews(R)
(c) 2009 The Thomson Corporation. All rights reserved.
19345838 Biosis No.: 200700005579
Bone implants with central chambers

Author: Anonymous; Paul David C; Emch Hansjuerg W; Schenk Beat; Boyer Michael

L; Higgins Thomas B

Author Address: Phoenixville, PA USA**USA

Journal: Official Gazette of the United States Patent and Trademark Office

Patents AUG 8 2006 2006

ISSN: 0098-1133

Document Type: Patent Record Type: Abstract Language: English

Abstract: A **bone** fusion **implant** for repair or replacement of **bone** includes a hollow body formed from at least two **bone** fragments which are configured and dimensioned for mutual engagement and which are coupled together. The hollow body may be formed of **autograft**, **allograft**, or **xenograft bone tissue**, and may include a core formed of at least one of **bone** material and **bone** inducing substances, with the core being disposed in the hollow body.

12/7/35 (Item 7 from file: 5) <u>Links</u>
Biosis Previews(R)
(c) 2009 The Thomson Corporation. All rights reserved.
18923315 Biosis No.: 200600268710
End member for a bone fusion implant

Author: Messerli Dominique D; Paul David C Author Address: W Chester, PA USA**USA

Journal: Official Gazette of the United States Patent and Trademark Office

Patents AUG 16 2005 2005

ISSN: 0098-1133

Document Type: Patent Record Type: Abstract Language: English

Abstract: An end member for use with a bone fusion implant is disclosed. The end member has a first portion, a second portion, and a shoulder connecting the two portions. The second portion is sized to fit within the interior of the bone fusion implant in such a fashion that the shoulder rests on the edge of the implant. The top surface of the first portion has at least one slot to receive a surgical instrument such as an inserter and/or distractor to facilitate implantation of the end member and bone fusion implant. The top surface may also have teeth to provide initial mechanical stability between the bone and end plate and promote bone fusion.

12/7/38 (Item 10 from file: 5) Links
Biosis Previews(R)
(c) 2009 The Thomson Corporation. All rights reserved.
17555112 Biosis No.: 200300523831

Author: Boyer Michael L (Reprint); Paul David C; Higgins Thomas B

Author Address: Paoli, PA, USA**USA

Implants formed of coupled bone

Journal: Official Gazette of the United States Patent and Trademark Office

Patents 1275 (2): Oct. 14, 2003 2003

Medium: e-file

ISSN: 0098-1133 _(ISSN print)

Document Type: Patent Record Type: Abstract Language: English

Abstract: The present invention relates to an **implant** comprising two or more bone fragments that are combined to form a single unit. Cancellous bone or cortical bone is removed from a source and fashioned into bone components with desirable shapes and sizes. The bone components may be integrated to form **implants** for **implantation** in the body. Bone stock may be formed by combining sections of various bones of the body, and the bone stock may be further fashioned for use as **implants** with particular geometries.

NPL Database Search - #1

Search Strategy

```
Set
        Items
               Description
S1
       281742
               S (BONE OR BONES OR BONY OR BONEY OR OSSEOUS? OR OSTEAL? OR
OSTEO? OR (HARD OR SKELETAL?) (3N) TISSUE? ? OR CANCELLOUS? OR CORTICAL? ? OR
CORTICOCANCELLOUS? OR TRABECULAR? ?) (5N) (BLOCK? ? OR PLUG OR PLUGS OR
PLUGGING OR PLUGGED OR MASS OR SHEET? ? OR IMPLANT? OR GRAFT? OR ALLOGRAFT?
OR HOMOGRAFT? OR AUTOGRAFT? OR XENOGRAFT? OR (HOMOLOGOUS? OR ALLOGENEIC? OR
AUTOGEN? OR XENOGEN? OR HOMOGEN?) (3N) TRANSPLANT?)
         2355
               S WET OR WETS OR WETTING OR WETTED OR WASH??? OR DAMP OR
DAMPEN? OR (HCL OR HYDROCHLORIC? OR ACID??) (2N) TREAT?
S3
         1846 S SUBMERS? OR IMMERS? OR HYDRAT?
S4
        3373 S SOFTEN? OR SPONGE? OR SPONGI?
S5
        12877
              S COMPRESS? OR PACK? ? OR PACKED OR PACKING OR COMPACT? OR
TAMP?? OR TAMPING
        9966
              S MOLD??? OR SHAPE? ? OR SHAPING OR RESHAP??? OR (DECREAS? OR
REDUC?)(2N)(SIZE? ? OR SIZING)
         7891 S HARDEN? OR INDURAT? OR DRY? ? OR DRYING OR DRIED OR DRIES
S7
OR HEAT??? OR FREEZEDRY? OR FREEZEDRIE? OR DEHYDRAT?
S8
         135 S S2:S4(S)S5(S)S6:S7
S9
       212068 S S1/TI,AB
S10
          97 S S8 AND S9
S11
           42 RD
                   (unique items)
S12
           38 S S8 NOT S10
S13
          33 RD (unique items)
S14
       12996
               S S1 (10N) (MANUFACTUR? OR PREPAR? OR PROCESS??? OR
PRODUCTION? OR PRODUCE? ? OR PRODUCING)
        1294 S S14/TI
S16
        7411
               S S1 (10N) (MANUFACTUR? OR PREPARATION? OR PREPARING OR
PREPARE? ? OR PRODUCTION? OR PRODUCE? ? OR PRODUCING)
         714
S17
               S S16/TI
               S S17 AND S2:S7
         108
S18
S19
          108
               S S18 NOT (S8 OR S12)
          54 RD (unique items)
S20
S21
         599 S S2:S4(S)S5
S22
        1059 S S2:S4(S)S6:S7
        1332 S S5(S)S6:S7
S23
S24
         234
               S S14(S)S21:S23
S25
          209
              S S24 NOT (S8 OR S12 OR S19)
[File 155] MEDLINE(R) 1950-2009/Mar 16
(c) format only 2009 Dialog. All rights reserved.
[File 73] EMBASE 1974-2009/Mar 17
(c) 2009 Elsevier B.V. All rights reserved.
[File 5] Biosis Previews(R) 1926-2009/Mar W3
(c) 2009 The Thomson Corporation. All rights reserved.
[File 91] MANTIS (TM) 1880-2008/Aug
2001 (c) Action Potential. All rights reserved.
[File 164] Allied & Complementary Medicine 1984-2009/Mar
(c) 2009 BLHCIS. All rights reserved.
[File 45] EMCare 2009/Mar W2
(c) 2009 Elsevier B.V. All rights reserved.
[File 23] CSA TECHNOLOGY RESEARCH DATABASE 1963-2009/MAR
(c) 2009 CSA. All rights reserved.
```

```
[File 24] CSA Life Sciences Abstracts 1966-2009/May
(c) 2009 CSA. All rights reserved.
[File 8] Ei Compendex(R) 1884-2009/Mar W1
(c) 2009 Elsevier Eng. Info. Inc. All rights reserved.
[File 144] Pascal 1973-2009/Mar W2
(c) 2009 INIST/CNRS. All rights reserved.
[File 467] ExtraMED(tm) 2000/Dec
(c) 2001 Informania Ltd. All rights reserved.
[File 35] Dissertation Abs Online 1861-2009/Feb
(c) 2009 ProQuest Info&Learning. All rights reserved.
[File 65] Inside Conferences 1993-2009/Mar 18
(c) 2009 BLDSC all rts. reserv. All rights reserved.
[File 148] Gale Group Trade & Industry DB 1976-2009/Mar 05
(c) 2009 Gale/Cengage. All rights reserved.
[File 149] TGG Health&Wellness DB(SM) 1976-2009/Feb W2
(c) 2009 Gale/Cengage. All rights reserved.
[File 441] ESPICOM Pharm&Med DEVICE NEWS 2009/Jan W2
(c) 2009 ESPICOM Bus. Intell. All rights reserved.
```

Search Results

```
11/7/19 (Item 1 from file: 5) <u>Links</u>
Biosis Previews(R)
(c) 2009 The Thomson Corporation. All rights reserved.
17855128 <u>Biosis No.:</u> 200400225183
Spinal intervertebral implant and method of making
```

Author: Shimp Lawrence A (Reprint); Annunziato Steven; Martz Erik; Kaes David

Author Address: Monmouth Beach, NJ, USA**USA

Journal: Official Gazette of the United States Patent and Trademark Office

Patents 1280 (3): Mar. 16, 2004 2004

Medium: e-file

ISSN: 0098-1133 _(ISSN print)

Document Type: Patent Record Type: Abstract Language: English

Abstract: A C-shaped or ring shaped implant formed of cortical bone has its C-shaped or inner channel filled with a bone promoting material which is preferably demineralized bone fibers formed as a flexible wet sheet or may be cancellous bone, pressed bone fibers formed from demineralized cortical bone chips soaked in acid, or a flex material formed of demineralized bone growth promoting bone fibers. The discrete bone filler element may be secured by a bonding agent, pins or screws, metal, polymer or bone material. The bone filler material is preferably bonded by filling a section of a long bone medullary cavity with wet bone fibers and then drying the fibers to bond them to the outer bone. A filled bone ring may be sliced to form annular filled sections which are then divided into mirror image C-shaped halves each forming an implant. Flex material of compressed bone fibers may be formed with an opening shaped to receive a cortical bone implant element having a C-shaped channel. The flex material surrounds the cortical bone element and fills its channel. Other embodiments are disclosed.

20/7/15 (Item 15 from file: 155) **Links** Fulltext available through: STIC Full Text Retrieval Options MEDLINE (R) (c) format only 2009 Dialog. All rights reserved. 11409088 **PMID:** 7774435 [Progress in the preparation of bone allografts and their clinical uses] Song S Q Zhonghua wai ke za zhi Chinese journal of surgery (CHINA) Dec 1994 , (12) p771-4 , **ISSN:** 0529-5815--Print **Journal Code:** 0153611 Publishing Model Print Document type: Comparative Study; Journal Article; Review Languages: CHINESE Main Citation Owner: NLM Record type: MEDLINE; Completed (32 Refs.) Record Date Created: 19950707 Record Date Completed: 19950707 20/7/25 (Item 25 from file: 155) Links Fulltext available through: STIC Full Text Retrieval Options MEDLINE (R) (c) format only 2009 Dialog. All rights reserved. 03205226 **PMID:** 5341653 [Enhancement of the accretion of the Kiel compact bone graft preparation] A kieli kemenycsontkeszitmeny beepulesi keszsegenek fokozasa. Kondrai G; Tarsoly E Orvosi hetilap (HUNGARY) Sep 11 1966 , 107 (37) p1747-9 , ISSN: 0030-6002--Print Journal Code: 0376412 Publishing Model Print Document type: In Vitro; Journal Article Languages: HUNGARIAN Main Citation Owner: NLM Record type: MEDLINE; Completed Record Date Created: 19671028 Record Date Completed: 19671028 20/7/36 (Item 7 from file: 5) **Links** Biosis Previews(R) (c) 2009 The Thomson Corporation. All rights reserved. 16919411 **Biosis No.:** 200200512922 Process for producing flexible sheets from demineralized, elongate, bone particles Author: Dowd Michael (Reprint); Scarborough Nelson L; Daugherty Mark; McMickle Jack Author Address: Eastampton, NJ, USA**USA Journal: Official Gazette of the United States Patent and Trademark Office Patents 1261 (3): Aug. 20, 2002 2002 Medium: e-file **ISSN:** 0098-1133 Document Type: Patent

Record Type: Abstract Language: English

Abstract: A process for fabricating shaped material from demineralized bone particles includes the steps of applying a liquid slurry of demineralized bone particles to a support, removing excess liquid form the demineralized bone particles to provide a cohering shaped mass of demineralized bone particles, and warming the shaped mass of demineralized bone particles at a predetermined temperature and for a predetermined time period. The resultant bone mass exhibits enhanced tensile strength and minimal bone particle disassociation upon rehydration thereby improving product handling and application at the operative site.

20/7/47 (Item 8 from file: 23) Links
CSA TECHNOLOGY RESEARCH DATABASE
(c) 2009 CSA. All rights reserved.
0003242129 IP Accession No: CA6705671

Method of producing implantable bone replacement materials

Publication Date: 1987

, US US

Document Type: Patent
Record Type: Citation
Language: English

Notes: Patent date: 27 Oct 1987; Patent date: 27 Oct 1987 File Segment: Ceramics Abstracts/World Ceramic Abstracts

?

NPL Database Search - #2

Search Strategy

```
Set
        Items
               Description
       281742
S1
               S (BONE OR BONES OR BONY OR BONEY OR OSSEOUS? OR OSTEAL? OR
OSTEO? OR (HARD OR SKELETAL?) (3N) TISSUE? ? OR CANCELLOUS? OR CORTICAL? ? OR
CORTICOCANCELLOUS? OR TRABECULAR? ?) (5N) (BLOCK? ? OR PLUG OR PLUGS OR
PLUGGING OR PLUGGED OR MASS OR SHEET? ? OR IMPLANT? OR GRAFT? OR ALLOGRAFT?
OR HOMOGRAFT? OR AUTOGRAFT? OR XENOGRAFT? OR (HOMOLOGOUS? OR ALLOGENEIC? OR
AUTOGEN? OR XENOGEN? OR HOMOGEN?) (3N) TRANSPLANT?)
         2355
               S WET OR WETS OR WETTING OR WETTED OR WASH??? OR DAMP OR
DAMPEN? OR (HCL OR HYDROCHLORIC? OR ACID??) (2N) TREAT?
S3
        1846 S SUBMERS? OR IMMERS? OR HYDRAT?
S4
        3373 S SOFTEN? OR SPONGE? OR SPONGI?
S5
       12877
              S COMPRESS? OR PACK? ? OR PACKED OR PACKING OR COMPACT? OR
TAMP?? OR TAMPING
        9966
              S MOLD??? OR SHAPE? ? OR SHAPING OR RESHAP??? OR (DECREAS? OR
REDUC?)(2N)(SIZE? ? OR SIZING)
         7891 S HARDEN? OR INDURAT? OR DRY? ? OR DRYING OR DRIED OR DRIES
S7
OR HEAT??? OR FREEZEDRY? OR FREEZEDRIE? OR DEHYDRAT?
S8
         7411
               S S1 (10N) (MANUFACTUR? OR PREPARATION? OR PREPARING OR
PREPARE? ? OR PRODUCTION? OR PRODUCE? ? OR PRODUCING)
         599 S S2:S4(S)S5
        1059 S S2:S4(S)S6:S7
S10
        1332 S S5(S)S6:S7
S11
         152 S S8(S)S9:S11
S12
              RD (unique items)
S13
          70
S14
        5765
              S S1(10N) PROCESS?
          95
S15
              S S14(S)S9:S11
S16
           82 S S15 NOT S12
S17
          39
              RD (unique items)
[File 155] MEDLINE(R) 1950-2009/Mar 16
(c) format only 2009 Dialog. All rights reserved.
[File 73] EMBASE 1974-2009/Mar 17
(c) 2009 Elsevier B.V. All rights reserved.
[File 5] Biosis Previews(R) 1926-2009/Mar W3
(c) 2009 The Thomson Corporation. All rights reserved.
[File 91] MANTIS (TM) 1880-2008/Aug
2001 (c) Action Potential. All rights reserved.
[File 164] Allied & Complementary Medicine 1984-2009/Mar
(c) 2009 BLHCIS. All rights reserved.
[File 45] EMCare 2009/Mar W2
(c) 2009 Elsevier B.V. All rights reserved.
[File 23] CSA TECHNOLOGY RESEARCH DATABASE 1963-2009/MAR
(c) 2009 CSA. All rights reserved.
[File 24] CSA Life Sciences Abstracts 1966-2009/May
(c) 2009 CSA. All rights reserved.
[File 8] Ei Compendex(R) 1884-2009/Mar W1
(c) 2009 Elsevier Eng. Info. Inc. All rights reserved.
[File 144] Pascal 1973-2009/Mar W2
(c) 2009 INIST/CNRS. All rights reserved.
[File 467] ExtraMED(tm) 2000/Dec
(c) 2001 Informania Ltd. All rights reserved.
```

[File 35] Dissertation Abs Online 1861-2009/Feb
(c) 2009 ProQuest Info&Learning. All rights reserved.
[File 65] Inside Conferences 1993-2009/Mar 18
(c) 2009 BLDSC all rts. reserv. All rights reserved.
[File 148] Gale Group Trade & Industry DB 1976-2009/Mar 05
(c) 2009 Gale/Cengage. All rights reserved.
[File 149] TGG Health&Wellness DB(SM) 1976-2009/Feb W2
(c) 2009 Gale/Cengage. All rights reserved.
[File 441] ESPICOM Pharm&Med DEVICE NEWS 2009/Jan W2
(c) 2009 ESPICOM Bus.Intell. All rights reserved.

Search Results

No relevant results.

Foreign & International Patent Search

(c) 2009 JPO & JAPIO. All rights reserved.

Search Strategy

```
Description
Set
       Items
               S (BONE OR BONES OR BONY OR BONEY OR OSSEOUS? OR OSTEAL? OR
S1
        14228
OSTEO? OR (HARD OR SKELETAL?) (3N) TISSUE? ? OR CANCELLOUS? OR CORTICAL? ? OR
CORTICOCANCELLOUS? OR TRABECULAR? ?) (5N) (BLOCK? ? OR PLUG OR PLUGS OR
PLUGGING OR PLUGGED OR MASS OR SHEET? ? OR IMPLANT? OR GRAFT? OR ALLOGRAFT?
OR HOMOGRAFT? OR AUTOGRAFT? OR XENOGRAFT? OR (HOMOLOGOUS? OR ALLOGENEIC? OR
AUTOGEN? OR XENOGEN? OR HOMOGEN?) (3N) TRANSPLANT?)
        1139
              S WET OR WETS OR WETTING OR WETTED OR WASH??? OR DAMP OR
DAMPEN? OR (HCL OR HYDROCHLORIC? OR ACID??) (2N) TREAT?
         848 S SUBMERS? OR IMMERS? OR HYDRAT?
S3
          426 S SOFTEN? OR SPONGE? OR SPONGI?
S4
S5
        1735 S COMPRESS? OR PACK? ? OR PACKED OR PACKING OR COMPACT? OR
TAMP?? OR TAMPING
         3984 S MOLD??? OR SHAPE? ? OR SHAPING OR RESHAP??? OR (DECREAS? OR
S6
REDUC?)(2N)(SIZE? ? OR SIZING)
         2536 S HARDEN? OR INDURAT? OR DRY? ? OR DRYING OR DRIED OR DRIES
OR HEAT??? OR FREEZEDRY? OR FREEZEDRIE? OR DEHYDRAT?
         159 S S2:S4(S)S5(S)S6:S7
S9
         245 S S2:S4(S)S5
        1090 S S2:S4(S)S6:S7
S10
S11
         714 S S5(S)S6:S7
S12
        4450 S S1/TI, DE
S13
          63 S S8 AND S12
         375
              S S2:S4(5N)(BLOCK? ? OR PLUG OR PLUGS OR PLUGGING OR PLUGGED
OR MASS OR SHEET? ? OR IMPLANT? OR GRAFT? OR ALLOGRAFT? OR HOMOGRAFT? OR
AUTOGRAFT? OR XENOGRAFT? OR (HOMOLOGOUS? OR ALLOGENEIC? OR AUTOGEN? OR
XENOGEN? OR HOMOGEN?) (3N) TRANSPLANT?)
S15
          502
               S S5(5N)(BLOCK? ? OR PLUG OR PLUGS OR PLUGGING OR PLUGGED OR
MASS OR SHEET? ? OR IMPLANT? OR GRAFT? OR ALLOGRAFT? OR HOMOGRAFT? OR
AUTOGRAFT? OR XENOGRAFT? OR (HOMOLOGOUS? OR ALLOGENEIC? OR AUTOGEN? OR
XENOGEN? OR HOMOGEN?) (3N) TRANSPLANT?)
        1710
               S S6:S7 (5N)(BLOCK? ? OR PLUG OR PLUGS OR PLUGGING OR PLUGGED
OR MASS OR SHEET? ? OR IMPLANT? OR GRAFT? OR ALLOGRAFT? OR HOMOGRAFT? OR
AUTOGRAFT? OR XENOGRAFT? OR (HOMOLOGOUS? OR ALLOGENEIC? OR AUTOGEN? OR
XENOGEN? OR HOMOGEN?) (3N) TRANSPLANT?)
          25
              S S14 AND S15 AND S16
S17
S18
          15
              S S17 NOT S13
S19
          42 S S14 AND S15
S20
         156
              S S14 AND S16
         146 S S15 AND S16
S21
S22
         125
              S S20:S21 AND S12
         113
S23
               S (S19 OR S22) NOT (S13 OR S18)
S24
         159
               S S9 AND S10 AND S11
S25
         87
               S S24 NOT (S13 OR S18 OR S22)
[File 350] Derwent WPIX 1963-2008/UD=200915
(c) 2009 Thomson Reuters. All rights reserved.
[File 347] JAPIO Dec 1976-2008/Oct(Updated 090220)
```

Search Results

13/25,K/4 (Item 4 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0018278039

WPI Acc no: 2008-L98374/200870

Related WPI Acc No: 2000-558372; 2003-429392; 2008-A95080

XRAM Acc no: C2008-362920 XRPX Acc No: N2008-881895

Load-bearing osteoimplant useful for repair of bone defects comprises a shaped, coherent mass of bone particles comprising combination of nondemineralized and demineralized bone and having specific bulk density and wet compressive strength

Patent Assignee: BOYCE T M (BOYC-I); MANRIQUE A (MANR-I); SHIMP L A (SHIM-I); WINTERBOTTOM J W (WINT-I)

Inventor: BOYCE T M; MANRIQUE A; SHIMP L A; WINTERBOTTOM J W

Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Type
US 20080188945	A1	20080807	200870	В

US 20080188945

Local Applications (no., kind, date): US 1999256447 A 19990223; US 2001911562 A 20010724; US 2002229767 A 20020827; US 2003736799 A 20031216 Priority Applications (no., kind, date): US 1999256447 A 19990223; US 2001911562 A 20010724; US 2002229767 A 20020827; US 2003736799 A 20031216

Alerting Abstract US A1

NOVELTY - A load-bearing **osteoimplant** (P1) comprises a **shaped**, coherent **mass** of **bone** particles possessing a bulk density of greater than 0.7 g/cm³ and a **wet compressive** strength of at least 3 MPa; where the **bone** particles comprise a combination of nondemineralized and demineralized **bone**.

DESCRIPTION - INDEPENDENT CLAIMS are included for the following:

producing (M1) the load-bearing osteoimplant involving: (a) providing an aggregate containing bone particles, and optional components selected from binder, filler, plasticizer, wetting agent, surface active agent, biostatic/biocidal agent, bioactive substance, reinforcing material and/or reinforcing structure; and, (b) shaping the aggregate into a coherent mass in at least one shaping operation to provide a shaped composite having an initial configuration for subsequent shaping into a desired osteoimplant or a final configuration corresponding to that of the osteoimplant; and an integral implant insertion instrument and implant comprising an implant insertion instrument portion integrally attached to an implant portion by a weakened, break-away connection such that on insertion of the implant portion at the implantation site, the implant insertion instrument portion is separated from the implant portion by a breaking-away force applied to it, where the implant portion is the load-bearing osteoimplant (P1) comprising a shaped, coherent mass of bone particles.

ACTIVITY - **Osteo**pathic. No biological data given. MECHANISM OF ACTION - None given.

USE - As load-bearing **osteoimplant**s (claimed), useful for incorporation or **implant**ation into body for repair of **bone** defects and injuries.

ADVANTAGE - The **osteoimplant** can assume any desired **shape**; can provide structural support to the site; and promotes new host **bone tissue** formation. The **osteoimplant** possesses a **wet compressive** strength of 12-200 (preferably 15-130, especially 20-200 or 31-200, particularly 56-200) MPa.

Load-bearing osteoimplant useful for repair of bone defects comprises a shaped, coherent mass of bone particles comprising combination of nondemineralized and demineralized bone and having specific bulk density and wet compressive strength Alerting Abstract ... NOVELTY - A load-bearing osteoimplant (P1) comprises a shaped, coherent mass of bone particles possessing a bulk density of greater than 0.7 g/cm3 and a wet compressive strength of at least 3 MPa; where the bone particles comprise a combination of nondemineralized and demineralized bone.... producing (M1) the loadbearing osteoimplant involving: (a) providing an aggregate containing bone particles, and optional components selected from binder, filler, plasticizer, wetting agent, surface active agent, biostatic/biocidal agent, bioactive substance, reinforcing material and/or reinforcing structure; and, (b) shaping the aggregate into a coherent mass in at least one shaping operation to provide a **shaped** composite having an initial configuration for subsequent shaping into a desired osteoimplant or a final configuration corresponding to that of the osteoimplant; and an integral implant insertion instrument and implant comprising an implant... ... separated from the implant portion by a breaking-away force applied to it, where the implant portion is the loadbearing osteoimplant (P1) comprising a shaped, coherent mass of bone particles... ... ADVANTAGE - The osteoimplant can assume any desired shape; can provide structural support to the site; and promotes new host bone tissue formation. The osteoimplant possesses a wet compressive strength of 12-200 (preferably 15-130, especially 20-200 or 31-200, particularly 56-200) MPa.Technology Focus PHARMACEUTICALS - Preferred Method: The shaping step (b) of the method (M1) further involves initial **shaping** of the aggregate into an osteoimplant blank and a subsequent shaping of the osteoimplant blank into a fully shaped osteoimplant. The shaping of the aggregate is accomplished by compressing the aggregate within a mold, optionally at elevated temperature. The aggregate is **shaped** at least in part by **molding**, casting, computer aided design/computer aided manufacturing (CAD/CAM) operation, by rolling, by vacuum-forming, by sintering, by melt-forming, by thermoforming, by foam molding, by forging, or by laser fusion of polymer binder in it. The molding is by injection molding, blow molding, rotational molding, leach molding, or leavening molding. The casting is by solvent casting or gel casting. Subsequent shaping of the blank into the fully shaped osteoimplant includes a machining operation. The **shaping** by CAD/CAM operation further involves: (al) imaging a patient's implantation site to provide digital information for a three dimensional model of an osteoimplant... ... computer; and (c1) machining a blank which is a coherent **mass** of an aggregate containing **bone** particles and, optional components selected from binder, filler, plasticizer, wetting agent, surface active agent, biostatic/biocidal agent, bioactive substance, reinforcing material and reinforcing structure to provide the osteoimplant, the machining is carried out by a machine executing a defined tool path numerically controlled by the computer in which the CAD file is stored. The shaping by CAD/CAM operation further involves: (a2) imaging a patient's implantation site to provide digital information for a three dimensional model of an osteoimplant... ... at the site; (b2) converting the three dimensional model of the osteoimplant into a CAD file stored in memory of a computer; (c2) forming a mold whose shaping surface conforms to the osteoimplant using the CAD file; and (d2) forming the osteoimplant in the mold. The imaging step is carried out by computerized axial tomography (CAT)

scan, magnetic resonance imaging (MRI), or medical ultrasound imaging (MUI). The binder present in... Extension Abstract ...using HCl solution (0.6 N, 14 ml). The acid was allowed to react to exhaustion (pH 7). The partially demineralized elongate bone particles were washed in water, and placed into a 13 mm cylindrical press-mold. The filled mold was placed in a heated water bath and heated continuously to 70(deg) C during the pressing process. The bone particles were pressed at 120000 psi for 3 days. The pellet produced was placed in a -70(deg) C freezer for 1 hour, then freeze-dried for 24 hours to obtain an osteoimplant. The resulting osteoimplant had a bulk density of 1.9 g/cm3. The osteoimplant was rehydrated overnight in physiological saline and then tested for wet compressive strength. The osteoimplant had wet compressive strength of 56.4 MPa.Title Terms .../Index Terms/Additional Words: SHAPE;WET; COMPRESS; Class Codes

13/25,K/15 (Item 15 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0015606931

WPI Acc no: 2006-171103/200618

Related WPI Acc No: 2002-268901; 2003-554818

XRAM Acc no: C2006-057396 XRPX Acc No: N2006-147586

Osteoimplant, useful for repairing and/or treating bone defect, comprises a coherent aggregate of elongate bone particles, where the implant possess predetermined dimensions and shape

Patent Assignee: BODEN S D (BODE-I); EDWARDS J T (EDWA-I); MANRIQUE A (MANR-I); RUSSELL J L (RUSS-I); SCARBOROUGH N L (SCAR-I); SHIMP L A (SHIM-I); TRAIANEDES K (TRAI-I)

Inventor: BODEN S D; EDWARDS J T; MANRIQUE A; RUSSELL J L; SCARBOROUGH N L; SHIMP L A ; TRAIANEDES K

Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Type
US 20060030948	A1	20060209	200618	В

US 20060030948

Local Applications (no., kind, date): US 2000219198 P 20000719; US 2001288212 P 20010502; WO 2001US22853 A 20010719; US 2002137862 A 20020502; US 2005231954 A 20050921

Priority Applications (no., kind, date): US 2000219198 P 20000719; US 2001288212 P 20010502; WO 2001US22853 A 20010719; US 2002137862 A 20020502; US 2005231954 A 20050921

Alerting Abstract US A1

NOVELTY - Osteoimplant (I) comprises a coherent aggregate of elongate bone particles, where (I) possess predetermined dimensions and shape.

DESCRIPTION - INDEPENDENT CLAIMS are also included for:

an implant (II) for bone repair possessing at least one cavity containing (I);

a method of making an **osteoimplant** comprising providing a quantity of elongate **bone** particles; mixing the elongate **bone** particles with an aqueous **wetting** agent to provide **a fluid** composition containing 5-40 volume percent swollen, **hydrated** elongate **bone** particles; **introducing** the **fluid** composition into a **mold**; and removing aqueous **wetting** agent to provide **a** coherent

aggregate of elongate **bone** particles possessing the dimensions and **shape** of the **osteoimplant**;

a method of making a plug for insertion in a cavity of an implant or bone defect site, comprising: providing a coherent aggregate of elongate bone particles; lyophilizing the coherent aggregate of elongate bone particles or subjecting the coherent aggregate of elongate bone particles to a compressive force; and forming the (compressed) coherent aggregate of elongate bone particles into the plug before or after carrying out the lyophilizing step; or providing a coherent aggregate of elongate bone particles at least some of which possess surface-exposed collagen; crosslinking elongate bone particles in the coherent aggregate through their mutually-contacting surface exposed collagen; and shaping the cross linked coherent aggregate of elongate bone particles into the plug before or after carrying out crosslinking step; a method of treating a bone defect in which the bone defect site possesses at least one cavity, comprising: providing a coherent aggregate of elongate bone particles; subjecting the coherent aggregate of elongate bone particles to a compressive force; and forming the compressed coherent aggregate of elongate bone particles into the plug before or after carrying out the subjecting step; or inserting a plug in the cavity, the plug comprising a coherent aggregate of elongate bone particles sized and shaped to substantially fill the cavity;

a method **of** fusing adjacent vertebrae comprising providing a space between adjacent vertebrae to be fused; and **implant**ing (I) in the space; and a method of repairing and/or **treat**ing **bone** comprising **implant**ing (I) at a **bone** repair site.

ACTIVITY - Osteopathic.

MECHANISM OF ACTION - None given.

USE - (I) is useful for repairing and/or treating bone defect, where the repaired bone is ethmoid, frontal, nasal, occipital, parietal, temporal, mandible, maxilla, zygomatic, cervical vertebra, thoracic vertebra, lumar vertebra, scarum, rib, sternum, clavicle, scapula, humerus, radius, ulna, carpal bones, metacarpal bones phalanges, ilium, ischium, pubis, femur, tibia, fibula, patella, calcaneus, tarsal or metatarsal bones (claimed). (I) (can be fashioned as a plug for insertion in a space or cavity within an implant) is useful in an orthopedic procedure e.g. intervertebral spacer employed in spinal fusion or for insertion in a cavity associated with a relatively well-defined bone defect e.g. an extraction socket and a bore hole. The osteoinductive potential of (I) for posterolateral fusion was tested using rats. The results showed that (I) provided excellent osteoinductivity with a cohesive three-dimension, lower density and porous matrix

ADVANTAGE - (I) possess predetermined dimensions and **shape** (claimed). (I) is highly absorbent and **sponge**-like in nature. (I) can be **readily** applied to virtually any **bone** repair **site** in the body and can be utilized alone or in combination with one or more adjunct medical devices and/or procedures. (I) has unique ability to absorb body **fluid**s and still retain its original **shape**. (I) has excellent **osteo**inductivity.

Technology Focus ...acids. The elongate bone particles are in the lyophilized state; and are cross-linked. The aggregate of elongate bone particles has been subjected to a compressive force of up to about 100000 psi. The compressed aggregate of elongate bone particles is in the lyophilized state. (I) is swellable upon contact with body and/or irrigation fluids. (I) possessing an open pore structure and a bulk density of not greater than about 0.3 g/cm3. The elongate bone particles are demineralized. (I) is in the

shape of a sheet, plate, disk, cone, pin, screw, tube, tooth, tooth root,
plug, bone or portion of bone, wedge or portion of wedge, cylinder or
threaded cylinder. (I... Preferred Method: In the method of making an
osteoimplant, prior to removing aqueous wetting agent, the elongate bone
particles are heated; at least some of the elongate bone particles are
superficially demineralized, such elongate bone particles being bonded to
each other through cross-links formed in their mutually-contacting.... is
an intervertebral implant or fusion cage. The method of repairing and/or
treating bone comprises the implantation of the osteoimplant of (I)
dimensioned and shaped as an intervertebral implantExtension Abstract

13/25,K/22 (Item 22 from file: 350) <u>Links</u>
Fulltext available through: <u>Order File History</u>
Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0014814269

WPI Acc no: 2005-161958/200517 Related WPI Acc No: 2002-635509 XRAM Acc no: C2005-052365

Preparing osteogenic composition used in device for treating osteoporosis comprises combining purified collagen, osteoinductive substance and water containing dilute acid and forcing the combination to form a dispersion

Patent Assignee: ZIMMER ORTHOBIOLOGICS INC (ZIMM-N)

Inventor: DAMIEN C J

Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Туре
US 20050037978	A1	20050217	200517	В

US 20050037978

Local Applications (no., kind, date): US 2000747038 A 20001222; US 2004915995 A 20040811

Priority Applications (no., kind, date): US 2000747038 A 20001222; US 2004915995 A 20040811

Alerting Abstract US A1

NOVELTY - Preparing osteogenic composition comprising combining purified collagen, osteoinductive substance and water containing dilute acid in a dispersing assembly comprising two vessels connected by a **reduc**ed diameter portion to establish fluid communication between the vessels; and forcing the combination from vessel to vessel to form a dispersion, is new. DESCRIPTION - Preparation of an osteogenic composition (C1) comprises combining purified collagen, osteoinductive substance, and water containing dilute acid in a dispersing assembly comprising two vessels connected by a reduced diameter portion to establish fluid communication between the vessels; forcing the combination from vessel to vessel through the reduced diameter portion a predetermined number of times to disperse the collagen and osteoinductive substance in the water, such that the collagen is at least partially hydrated and a thickened dispersion is obtained; and allowing the dispersion to stand for a predetermined time interval. An INDEPENDENT CLAIM is also included for making an implantable osteogenic device involving dehydrating the extrudate of (C1) to yield a dehydrated osteogenic product; rehydrating the product; and mixing a bulking material with the rehydrated product to provide a shapeable osteogenic implant material or inserting the rehydrated product into a spinal cage to provide an osteogenic device.

ACTIVITY - Osteopathic; Cytostatic. No biological data given. MECHANISM OF ACTION - None given.

USE - The composition is used for **prepar**ing device useful for inducing **osteo**genesis at a site (e.g. dental or periodontal defect site) and in the disk space between two vertebral bodies (claimed); inducing **bone** formation of hip replacement operations and knee replacement operations; **treat**ing **osteo**porosis; and repairing **bone** tumor defects, cranialmaxillafacial defects and **bone** fractures.

ADVANTAGE - The collagen-based **osteo**genic materials has improved **shaping** and handling properties; and easy for the health care practitioner to use than conventional **implant**able **osteo**genic materials. The **shaped implant**able compositions or device provides a good matrix for the release of **osteo**genic substances and other desirable biologically active agents at the site of **implant**ation to promote **bone** growth. The composition is **compressed** and expanded to fill a defined defect or cage site; and has highly desirable physical properties such as improved cohesiveness, elasticity and ability to **mold** to a desired **shape**. The composition holds a desired **shape** better than conventional **osteo**genic compositions, permits the **shaped** composition or device to stay in place in an **implant** site better than other compositions or devices.

13/25,K/26 (Item 26 from file: 350) Links
Fulltext available through: Order File History
Derwent WPIX *** CURRENT APPLICATION ***

(c) 2009 Thomson Reuters. All rights reserved.

0014233573 & & Drawing available

WPI Acc no: 2004-419519/200439

Related WPI Acc No: 2002-740210; 2002-740212; 2002-740213; 2003-110482; 2004-728388; 2005-404640; 2009-A89861

Implant providing method for producing bone implant made from partially demineralized or demineralized bone, involves demineralizing block of cancellous bone having first geometry, before block is wet and compressed to second geometry

Patent Assignee: SYNTHES USA (SYNT-N)
Inventor: ANGELUCCI C M; BOYER M L; PAUL D C
Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Туре
US 20040107003	A1	20040603	200439	В

US 20040107003

Local Applications (no., kind, date): US 2001271745 P 20010228; US 2001927335 A 20010813; US 2003718804 A 20031124

Priority Applications (no., kind, date): US 2001271745 P 20010228; US 2001927335 A 20010813; US 2003718804 A 20031124

Alerting Abstract US A1

NOVELTY - The method involves demineralizing a **block** of **cancellous bone** (40) having a first geometry, before the **block** is **wet**. The **wet block** is **compress**ed from a first geometry to a second geometry.

USE - For **produc**ing **bone implant** made from partially demineralized or demineralized **bone** and used to **treat bone** fractures and defects.

 $\label{eq:advantage} \mbox{ADVANTAGE - Ensures reliable formation of \pmb{bone} from partially demineralized or demineralized \pmb{bone}.}$

DESCRIPTION OF DRAWINGS - The figure shows the isometric view of the **cortical** shell.

- 40 Block of cancellous bone
- 42 **Pellet**
- 44 Cylinder
- 46 Cage
- 48 Perforations

13/25,K/35 (Item 35 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0013341761 & & Drawing available WPI Acc no: 2003-429392/200340

Related WPI Acc No: 2000-558372; 2008-A95080; 2008-L98374

XRAM Acc no: C2003-113340 XRPX Acc No: N2003-342833

Load-bearing osteoimplant for repairing bone defects and injuries, and repairing hard tissues, in humans and animals, comprises shaped, coherent mass of bone particles

Patent Assignee: BOYCE T M (BOYC-I); MANRIQUE A (MANR-I); OSTEOTECH INC (OSTE-N); SHIMP L (SHIM-I); WINTERBOTTOM J M (WINT-I)

Inventor: BOYCE T M; MANRIQUE A; SHIMP L; WINTERBOTTOM J M

Patent Family (2 patents, 1 & countries)

Patent Number	Kind	Date	Update	Type
US 20030039676	A1	20030227	200340	В
US 6696073	B2	20040224	200415	E

US 20030039676

Local Applications (no., kind, date): US 1999256447 A 19990223; US 2001911562 A 20010724; US 2002229767 A 20020827; US 2002229767 A 20020827 Priority Applications (no., kind, date): US 1999256447 A 19990223; US 2001911562 A 20010724; US 2002229767 A 20020827

Alerting Abstract US A1

NOVELTY - A load-bearing **osteoimplant** (OI) (62) comprises a **shape**d, coherent **mass** of **bone** particles.

DESCRIPTION - INDEPENDENT CLAIMS are also included for:

production of load-bearing OI, which involve providing aggregate containing
bone particles and optionally with components such as binder, filler,
plasticizer, wetting agent, surface active agent, biostatic/biocidal agent,
bioactive substance, reinforcing material and/or reinforcing structure. The
aggregate is shaped into coherent mass in at least one shaping operation to
provide shaped composite having an initial configuration for subsequent
shaping into desired OI or a final configuration corresponding to OI; and
an integral implant insertion instrument and implant, comprises an implant
insertion instrument portion integrally attached to an implant portion (OI)
by a weakened, breakaway connection such that on insertion of OI portion at
the implantation site, the instrument portion is separated from the OI
portion by a break-away force was applied.

USE - For repairing **bone** defects and injuries, and also for repairing **hard tissue**s, in humans and animals.

ADVANTAGE - The **osteoimplant** (OI) possessing sufficient strength in body **fluid**s enables OI to bear loads. OI having pores or cavities permits

revascularization and enables incorporation in host. OI promotes formation of bone tissues within and around implant, and is capable of gradually transforming support loads to the host bone tissue as it remodels. The manufacture of OI is simple. OI obtained by the method has excellent bulk density, wet compressive strength, mechanical strength and is highly biocompatible.

DESCRIPTION OF DRAWINGS - The figure shows fibular wedged shaped load-bearing osteoimplant.

62 Load-bearing osteoimplant

Extension Abstract ...were mixed with an aqueous glycerol solution and soaked for 4-12 hours. The particles were then stained, placed in 28 mmdiameter cylindrical press mold and pressed at 10000 psi for 15 minutes. The obtained compressed pellet was heated for 4 hours at 45 (deg)C, to obtain an implant. OI was frozen at -70 (deg)C for 1.5 hours and freeze dried. Obtained OI had bulk density of 1.34 g/cm3, height of 29 nm and wet compressive strength of 3 MPa.Extension Abstract Image Original Publication Data by AuthorityArgentinaPublication No. ...Claims: What is claimed is:1. A loadbearing osteoimplant comprising a shaped, coherent mass of bone particles possessing a bulk density of greater than about 0.7 g/cm3 and a wet compressive strength of at least about 3 MPa.

13/25,K/38 (Item 38 from file: 350) **Links** Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0012880926 & & Drawing available

WPI Acc no: 2002-740213/200280

Related WPI Acc No: 2002-740210; 2002-740212; 2003-110482; 2004-419519; 2004-728388; 2005-404640; 2009-A89861

Forming method for demineralized bone implant, involves demineralizing cancellous bone section, then compressing bone section into smaller geometry and drying same bone section

Patent Assignee: ANGELUCCI C M (ANGE-I); BOYER M L (BOYE-I); PAUL D C (PAUL-I); SYNTHES (SYNT-N); SYNTHES USA (SYNT-N); SYNTHES GMBH (SYNT-N) Inventor: ANGELUCCI C M; BOYER M L; PAUL D C; ANGELUCCI C; BOYER M; PAUL D Patent Family (8 patents, 95 & countries)

Patent Number	Kind	Date	Update	Туре
US 20020120347	A1	20020829	200280	В
WO 2002069818	A2	20020912	200280	E
US 6652593	B2	20031125	200378	E
AU 2001283368	A1	20020919	200433	E
EP 1424948	A2	20040609	200438	E
AU 2001283368	A8	20051027	200624	E
EP 1424948	B1	20081210	200904	E
DE 60136971	E	20090122	200909	E

US 20020120347

Local Applications (no., kind, date): US 2001271745 P 20010228; US 2001927335 A 20010813; WO 2001US25455 A 20010814; US 2001927335 A 20010813; AU 2001283368 A 20010814; EP 2001962169 A 20010814; WO 2001US25455 A 20010814; AU 2001283368 A 20010814; EP 2001962169 A 20010814; WO 2001US25455 A 20010814; DE 60136971 A 20010814; EP 2001962169 A 20010814; WO 2001US25455 A 20010814

Priority Applications (no., kind, date): US 2001271745 P 20010228; US 2001271745 P 20010228; US 2001271745 P 20010228; US 2001927335 A 20010813; US 2001927333 A 20010813; US 2001927334 A 20010813; US 2001927335 A 20010813

Alerting Abstract US A1

NOVELTY - The method involves demineralizing a **cancellous bone** section of a predetermined geometry. The **bone** section is obtained from e.g. femur, tibia, humerus, fibula, ulna. The demineralized **bone** section is then **compress**ed to a smaller geometry and then **dried**. The **bone** section is then filled into a space, a **bony** defect or a cavity.

DESCRIPTION - INDEPENDENT CLAIMS are included for the following:

a method of maintaining distance between vertebral bodies; a method of replacing nucleus of a vertebral disc; and an **implant**.

USE - For forming demineralized **bone implant** for filling voids, **bone** defects or other regions e.g. cavities, within spinal cages, as well as **bony** defects caused by removal of **bone** screws or diseased **bone**. Also used as e.g. **cortical** shell, burr hole cover in cranial region of skull.

ADVANTAGE - Enables demineralized **cancellous bone** to be used as **soft** substance for enhancing anatomical areas during e.g. plastic surgery, face lifts, chin augmentations, cheek enhancements, eye brow lifts, or suited for filling defect regions caused by disease, congenital conditions or surgical procedure. Minimizes degree of brittleness of **bone**. Makes **implant** suitable in **treat**ment of brain problems e.g. tumors, aneurysm, blood clots, head injuries, abscesses, as well as medical procedures e.g. laminoplasty, nucleus replacements, disc or ligament replacement.

DESCRIPTION OF DRAWINGS - The figure shows the perspective view of a **cortical** shell.

Claims: An implant comprising demineralized cancellous bone, with the cancellous bone comprising a non-particulate portion of a bone, wherein the implant is capable of being softened and compressed into a smaller first shape and hardened in said first shape, and capable of expanding into a second shape larger than said first shape when resoftened and permitted to expand.

13/25,K/43 (Item 43 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0012395826

WPI Acc no: 2002-339519/200237

XRAM Acc no: C2002-097486 XRPX Acc No: N2002-266987

Treatment of monolithic bone, useful for conserving mechanical strength of monolithic bone e.g. implant or graft, comprises contacting bone with biocompatible mechanical strength-conserving agent, dehydrating and packaging

Patent Assignee: OSTEOTECH INC (OSTE-N)

Inventor: BOYCE T M; SHIMP L A

Patent Family (4 patents, 95 & countries)

Patent Number	Kind	Date	Update	Туре
WO 2002015948	A2	120020228	200237	В

AU	200186755	A	20020304	200247	E
EP	1311309	A2	20030521	200334	E
AU	2001286755	A8	20051013	200611	E

WO 2002015948

Local Applications (no., kind, date): WO 2001US26553 A 20010824; AU 200186755 A 20010824; EP 2001966222 A 20010824; WO 2001US26553 A 20010824; AU 2001286755 A 20010824

Priority Applications (no., kind, date): US 2000644521 A 20000824

Alerting Abstract WO A2

NOVELTY - Monolithic bone is treated by:

contacting the bone with a bio-compatible mechanical strength-conserving
agent(s) (BCMSCA);

dehydrating the bone; and
packaging the dehydrated bone.

The BCMSCA is an organic **liquid** which is capable of penetrating and remaining in the **bone** during its **dehydrat**ion, **pack**aging and storage.

DESCRIPTION - INDEPENDENT CLAIMS are also included for:

A rehydrated strength-conserved shaped bone implant, which is prepared by: contacting the bone with BCMSCA;

dehydrating the bone;

packaging the bone; and

rehydrating the packaged bone prior to or during implantation; and A method for the utilization of bone, for repairing ethmoid, frontal, nasal, occipital, parietal, temporal, mandible, maxilla, zygomatic, cervical vertebra, thoracic vertebra, lumbar vertebra, sacrum, rib, sternum, clavicle, scapula, humerus, radius, ulna, carpal bones, metacarpal bones, phalanges, ilium, ischium, pubis, femur, tibia, fibula, patella, calcaneus, tarsal and/or metatarsal bones comprises:

exposing a surgical site;

inserting the **bone** into the surgical site; and closing the surgical site.

USE - For conserving mechanical strength of monolithic **bone** useful as **implant** or **graft**, for repairing **bone**s, such as ethmoid, frontal, nasal, occipital, parietal, temporal, mandible, maxilla, zygomatic, cervical vertebra, thoracic vertebra, lumbar vertebra, sacrum, rib, sternum, clavicle, scapula, humerus, radius, ulna, carpal **bone**s, metacarpal **bone**s, phalanges, ilium, ischium, pubis, femur, tibia, fibula, patella, calcaneus, tarsal and/or metatarsal **bone**s (all claimed), in orthopedics, neurosurgery, oral and maxillofacial surgeries, joint reconstructions, repairs of vertebral column, repair of spinal injuries, fixation of fractures, discectomy, laminectomy, excision of spinal cord tumors, etc.

ADVANTAGE - The method of **treat**ing monolithic **bone** with mechanical strength-conserving agent, effectively conserves mechanical strength of **bone** during **dehydration**, **pack**aging and storage of **bones**. The method also maintains the **bone** strength throughout **rehydration** and **implant**ation of **bone** (claimed). The method **reduces** dimensional changes associated with lyophilization **of bone**, improves toughness of **bone grafts**, minimizes negative impact on the biological properties **of** the **bone grafts** and minimizes the tendency for a partially **rehydrated**-**dehydrated graft** to fracture due to insertion forces applied by the surgeon. The sonication of the agent and the **bone** effectively

improves the penetration property of the **agent into** the **bone tissue**s. The method which is rapid, effectively maintains the bio-mechanical properties of **bone**s, such as **compression** strength, flexural modulus, torsional modulus and yield strength.

The **treat**ed monolithic **bone** effectively demonstrates less shrinkage after **dehydration** than lyophilized **bone**. The bio-compatible and non-toxic agent utilized in the method effectively maintains the properties of **implant** for prolonged period, without causing any undesirable **changes** and does not interfere with normal healing of the **bone graft**. The mechanical strength-conserving agent which acts as antimicrobial/preservation agent effectively preserves shelf-life of **pack**aged **dehydrated bone** for prolonged period, and also acts as **wetting** agent to effectively **decreas**e rehdydration time.

13/25,K/51 (Item 51 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0010155517 & & Drawing available WPI Acc no: 2000-464322/200040

Related WPI Acc No: 1998-413678; 1998-427510; 2001-615401

XRAM Acc no: C2000-139820 XRPX Acc No: N2000-346454

Load bearing hard tissue implant for joining tissues or attaching surgical instruments comprises swellable implant body with channel for suture and load distributing device

Patent Assignee: NEUCOLL INC (NEUC-N)

Inventor: BROWN M K C; CASSIDY J J; CHU G H; RICE J; SCHROEDER J A; SHENOY V

N; YEUNG J E

Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Туре
US 6083522	A	20000704	200040	В

US 6083522

Local Applications (no., kind, date): US 1997781012 A 19970109; US 1997833874 A 19970410; US 19984550 A 19980108

Priority Applications (no., kind, date): US 1997781012 A 19970109; US 1997833874 A 19970410; US 19984550 A 19980108

Alerting Abstract US A

NOVELTY - A load bearing hard tissue implant comprises: a resorbable, swellable implant body with at least one hollow channel adapted to receive at least one suture; and a load-distributing device adapted to hold a suture. The implant body is made from a dehydrated crosslinked biocompatible polymer. DESCRIPTION - INDEPENDENT CLAIMS are included for:

preparation of an implant body for use in a load bearing implant device for hard tissue repair; and

methods for anchoring a surgical device into a **hard tissue** and for securing **hard tissue**s to each other using the **implant**.

USE - For joining **tissue**s or attaching surgical instruments (e.g. screws, rods or pins) to **hard tissue**, increasing its load bearing capacity DESCRIPTION OF DRAWINGS - The figure shows a perspective view of the **implant**:

- 1 Implant
- 2 Implant Body

- 3 Load Distributing Device
- 4 Suture

Technology Focus ...formaldehyde or glutaraldehyde) and/or a functionally activated synthetic hydrophilic polymer (especially multifunctionally activated polyethylene glycol). Alternatively, the crosslinking is non-covalent, carried out by drying, irradiating, heating or compressing. The biocompatible polymer is collagen, especially fibrillar collagen. The implant body also comprises... ... mixing a biocompatible polymer with a crosslinking agent; adding to a mold before crosslinking takes place; allowing to react in the mold to form a matrix; and drying to matrix to form a dehydrated implant body. Extension Abstract

13/25,K/53 (Item 53 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0009419335

WPI Acc no: 1999-356802/199930

XRAM Acc no: C1999-105451 XRPX Acc No: N1999-265614

Extrudable allograft bone tissue material for filling surgical sites

Patent Assignee: GERTZMAN A A (GERT-I); STEVENSON S (STEV-I)

Inventor: GERTZMAN A A; STEVENSON S

Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Туре
US 5910315	A	19990608	199930	В

US 5910315

Local Applications (no., kind, date): US 1997943549 A 19970718 Priority Applications (no., kind, date): US 1997943549 A 19970718

Alerting Abstract US A

NOVELTY - Extrudable, **shape** retaining semisolid **bone** composition made from mineralized/demineralized allo**graft bone** particles has sufficient internal cohesiveness and self-adhesion to be extrudable and yet retains the **shape** of the container from which it is extruded.

DESCRIPTION - A method for filling a surgical site with bone material comprises: placing a mass of lyophilized bone chips of predetermined mixed size of 100 microns to 2 mm, the chips including a packing of the interstitial spaces between the larger granular tissue particles of particulate cortical bone powder of 100-300 microns and larger sized granular tissue particles in a straight walled barrel of a syringe having a circular opening at the distal end of 8-15 mm diameter; tamping the mass of bone chips to fill air pockets in the syringe; adding a volume of sterile **fluid** of 3-6 times the bulk of the volume of the mass of bone chips to provide adequate wetting; allowing the fluid to flow through the mass of bone chips to fully hydrate the bone chips for a period of time hydrating the bone chips until the mass is fully reconstituted from its initial lyophilized state and obtains chip self-adherence conforming to the shape of the lumen of the barrel of the syringe and retain such shape and geometric integrity; draining sterile fluid from the syringe; and depressing the plunger of the syringe and extruding the shaped bone material in a semi-solid mass which retains its shape and integrity in a surgical site. INDEPENDENT CLAIMS are also included for: (1) a method of filling a surgical site with a shape-retaining, semisolid bone composition, the method comprises: placing a plurality of lyophilized bone particles of mixed sizes ranging from a particulate powder mixed with larger granular tissue particles. The lyophilized bone particles comprising a mixture containing 75 vol% of lyophilized, demineralized cortical/cancellous bone powder ranging from 0.5-2 mm particle size and 25 vol% of lyophilized, demineralized cortical bone powder ranging from 100-300 microns size to provide a bone composition with a packing of interstitial spaces between the larger granular tissue particle with particulate powder or other granular tissue particles in a straight-walled extrusion vessel having an opening at the distal end, the opening having the same dimensions as the interior of a spinal fusion chamber; pouring a volume of hydrating solution into an open proximal end of the extrusion vessel and allowing the solution to flow through the mass of the bone particles to fully hydrate the same; removing the air bubbles from the hydrating solution which adhere to the plurality of the bone particles; allowing the bone particles to hydrate for at least 20 minutes in the solution so that the **bone** particles become an extrudable, shape-retaining semi-solid mass; and extruding the bone particle composition from the extrusion vessel into the surgical site in a semi-solid shape which retains the shape of the interior of the vessel; (2) an extrudable, shape-retaining bone filler composition comprising: a mass of freeze dried demineralized bone particles having a particle size of 100-1000 microns, and packaged together with the smaller particles packing the interstitial spaces between the larger granular tissue particles in a walled container so that the interstices formed between the largest bone particles are filled; and a sterile hydrating agent having a volume of one to three to one to six in relation to the volume of the bone particle mass, and an elution speed through the bone particle mass of 2-6 minutes. The bone particle mass is placed in contact with the hydrating agent for at least 20 minutes to provide a swell volume of the bone particles of at least about 40%; and (3) an extrudable, **shape**-retaining **bone** filler composition comprising: a mass of freeze dried demineralized cancellous bone particles having a particle size of 250-420 microns, and packed together in a walled container so that the interstices between the largest bone particles are filled; and a sterile hydrating agent having a volume of one to three to one to six in relation to the volume of the bone particle mass, and an elution speed over 5 minutes and when immersing the bone particle mass, for at least 20 minutes to provides a swell volume of the **bone** particles of 50-150% . USE - The allograft bone powder composition is especially useful for use in surgery of the spinal column and other bone areas. ADVANTAGE - The composition has sufficient internal cohesiveness and selfadhesion to be extrudable and yet is capable of retaining the shape of the extrusion orifice. Optimum space filling is possible, the smaller particles filling the interstices between the larger particles. Use of chemical compounds is avoided thus avoiding adverse reactions in the patient.

Claims:placing a mass of lyophilized bone chips of predetermined mixed size ranging from 100 microns to 2.0 mm, said mass of chips including a packing of the interstitial spaces between the larger granular tissue particles of particulate cortical bone powder ranging from about 100 to about 300 microns and larger sized granular tissue particles..... walled barrel of a syringe having a circular opening at the distal end thereof, ranging from about 8 mm to about 15 mm in diameter; tamping the mass of bone chips to fill air pockets in the syringe; adding a volume of sterile fluid ranging from about 3 to about 6 times the bulk of the volume of the mass of bone chips to provide adequate wetting; allowing the fluid to flow through said mass of bone chip to filly hydrate the bone chips for a period of time hydrating the bone chips until the mass is fully reconstituted from its initial lyophilized state and

obtains chip self-adherence conforming to the **shape** of the lumen of the barrel of the syringe **and** retain such **shape** and geometric integrity; draining sterile **fluid** from the syringe; **and**depressing a plunger of the syringe and extruding the **shaped bone** material in a semi-solid **mass** which retains its **shape** and integrity **in** a surgical site.

13/25,K/55 (Item 55 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0009071914

WPI Acc no: 1998-427510/199836

Related WPI Acc No: 1998-413678; 2000-464322; 2001-615401

XRAM Acc no: C1998-128832 XRPX Acc No: N1998-333714

Load-bearing hard tissue implants for hard- tissue repair in mammals - comprise resorbable, swellable implant body consisting of dehydrated, crosslinked, biocompatible polymer, used e.g. to repair rotator cuffs

Patent Assignee: COHESION TECHNOLOGIES INC (COHE-N)

Inventor: BROWN M K; BROWN M K C; CASSIDY J J; CHU G H; RICE J; SCHROEDER J A; SHENOY V N; YEUNG J E

Patent Family (2 patents, 79 & countries)

Patent Number	Kind	Date	Update	Туре
WO 1998030141	A2	19980716	199836	В
AU 199860198	A	19980803	199850	E

WO 1998030141

Local Applications (no., kind, date): WO 1998US414 A 19980108; AU 199860198 A 19980108

Priority Applications (no., kind, date): US 1997781012 A 19970109; US 1997833874 A 19970410

Alerting Abstract WO A2

Load-bearing hard tissue implants comprise resorbable, swellable implant body consisting of a dehydrated, crosslinked, biocompatible polymer. Also claimed are (1) a method for joining second tissue to a first hard tissue in a mammal body, comprising (a) forming a cavity in the first tissue; (b) inserting a load-bearing implant into the cavity; (c) allowing the implant body to rehydrate in situ to anchor the implant into the first tissue; and (d) attaching a second tissue to the implant using the suture; (2) a method for anchoring surgical devices into hard tissue comprising (a) forming a cavity in the first tissue; (b) inserting a load-bearing implant comprising into the cavity; (c) inserting the surgical device into the implant; and (d) before or after (c) allowing the implant body to rehydrate in situ to anchor the implant into the hard tissue; and (3) a method for securing first and second hard tissues comprising (a) inserting at least one load-bearing implant into the hard tissues such that each load bearing implant transverses both hard tissues; and (b) allowing the implant body to rehydrate in situ to anchor the implant into the first and second tissues. USE - Implants are used in load-bearing devices for hard-tissue repair in mammals. They may be used to repair rotator cuffs (claimed). ADVANTAGE - As the implant bodies swell after insertion, the implants avoid the need for anchoring structures such as barbs, fins and wings. They may be combined with other surgical devices such as sutures, screws, pins and rods

to enhance the effectiveness of **tissue** repair. The **implant**s initially provide adequate mechanical integrity while later serving as a scaffold for **tissue** in-growth. The **implant**s are uniformly **shape**d and swellable.

Documentation Abstract Load-bearing hard tissue implants comprise resorbable, swellable implant body consisting of a dehydrated, crosslinked, biocompatible polymer... ... c) allowing the implant body to rehydrate in situ to anchor the implant into the first tissue; and... ... d) before or after (c) allowing the implant body to rehydrate in situ to anchor the implant into the hard tissue; and... ... b) allowing the implant body to rehydrate in situ to anchor the implant into the first and second tissues...effectiveness of tissue repair. The implants initially provide adequate mechanical integrity while later serving as a scaffold for tissue in-growth. The implants are uniformly shaped and swellable. The biocompatible polymer is noncovalently crosslinked. Crosslinking is achieved by drying, irradiating, heating or compression. The biocompatible polymer is collagen, preferably fibrillar collagen... ...b) introducing mixture into mould of desired shape before substantial crosslinking has occurred between the polymer and the crosslinking agent... ...d) drying the matrix to form a dehydrated implant body Documentation Abstract Image

13/25,K/58 (Item 58 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0008276480

WPI Acc no: 1997-385061/199735 XRAM Acc no: C1997-123417 XRPX Acc No: N1997-320606

Preparation of shaped material from bone particles - providing improved tensile strength and minimal bone particle disassociation upon rehydration

Patent Assignee: OSTEOTECH INC (OSTE-N)

Inventor: DAUGHERTY M; DOWD M; MCMICKLE J; SCARBOROUGH N; SCARBOROUGH N L
Patent Family (9 patents, 69 & countries)

Patent Number	Kind	Date	Update	Type
WO 1997025941	A1	19970724	199735	В
AU 199715350	A	19970811	199747	E
EP 880345	A1	19981202	199901	E
US 6436138	В1	20020820	200257	E
EP 880345	В1	20060405	200624	E
DE 69735625	E	20060518	200635	E
CA 2243365	С	20060725	200650	E
ES 2260783	Т3	20061101	200673	E
DE 69735625	Т2	20061221	200702	E

WO 1997025941

Local Applications (no., kind, date): WO 1997US644 A 19970116; AU 199715350 A 19970116; EP 1997901455 A 19970116; WO 1997US644 A 19970116; US 199610127 P 19960117; WO 1997US644 A 19970116; US 1998155064 A 19980918; EP 1997901455 A 19970116; WO 1997US644 A 19970116; DE 69735625 A 19970116; EP 1997901455 A 19970116; WO 1997US644 A 19970116; CA 2243365 A 19970116; WO 1997US644 A 19970116; DE 69735625 A 19970116; EP 1997901455 A 19970116; WO 1997US644 A 19970116; WO 1997US644 A 19970116; WO 1997US644 A 19970116; WO 1997US644 A 19970116

1998155064 A 19980918

Alerting Abstract WO A1

Preparation of shaped material from bone particles (BP) comprises: (a) applying a liquid slurry of BP to a support; (b) removing excess liquid to provide a coherent shaped mass; and (c) warming at a pre-determined temperature for a pre-determined time. The shaped mass prepared as above is claimed per se. Also claimed is a bone product comprising a coherent heat-treated shaped mass of demineralised, elongated bone particles.

USE - The demineralised bone powder is known to be useful in the repair of

USE - The demineralised **bone** powder is known to be useful in the repair of **bone** defects and for fabrication of **implants**.

ADVANTAGE - The **bone mass** exhibits enhanced tensile strength and minimal **bone** particle disassociation upon re**hydrat**ion thus improving **produc**t handling and application at the operative site. The **produc**t has improved capacity to maintain its cohesive properties and exhibit minimal **bone** particle disassociation upon re**hydrat**ion.

Documentation Abstract Preparation of shaped material from bone particles (BP) comprises... ... b) removing excess liquid to provide a coherent shaped mass; and... ... The shaped mass prepared as above is claimed per se... ... Also claimed is a bone product comprising a coherent heat-treated shaped mass of demineralised, elongated bone particles... ... ADVANTAGE - The bone mass exhibits enhanced tensile strength and minimal bone particle disassociation upon rehydration thus improving product handling and application at the operative site... ... The product has improved capacity to maintain its cohesive properties and exhibit minimal bone particle disassociation upon rehydration.... ... The warming step comprises placing the mould support and the **sheet** of DMBP into a **heating** device and **heating** to 22-55 (especially 45) (deg)C for 2-4 (especially 3) hours... ... The process includes drying the shaped mass subsequent to warming, preferably including lyophilisation.... The process further comprises compressing the shaped mass of DMBP during warming, preferably by placing a compressive cover on the mould to apply compressive forces to the sheet of DMBP. (SA) Documentation Abstract Image

18/25,K/9 (Item 9 from file: 350) <u>Links</u>
Fulltext available through: <u>Order File History</u>

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0012746302 & & Drawing available WPI Acc no: 2002-599178/200264 Related WPI Acc No: 2002-362852 XRPX Acc No: N2002-475290

Spinal implant for fusing adjacent vertebrae, has channel and fibrous bone element which is fitted into channel of discrete bone element of curved structure

Patent Assignee: OSTEOTECH INC (OSTE-N)

Inventor: ANNUNZIATO S; KAES D R; MARTZ E; SHIMP L A

Patent Family (3 patents, 2 & countries)

Patent Number	Kind	Date	Update	Туре
US 20020091447	A1	20020711	200264	В
US 6706067	В2	20040316	200420	E
AU 2002225831	A8	20050915	200569	E

Local Applications (no., kind, date): US 2000705377 A 20001103; US 20018279 A 20011105; US 20018279 A 20011105; AU 2002225831 A 20011102 Priority Applications (no., kind, date): US 2000705377 A 20001103; US 20018279 A 20011105

Alerting Abstract US A1

NOVELTY - A discrete **bone** element (10) exhibiting negligible **bone** growth factor, has a curved structure which forms a channel (26) with two side surfaces (32,34). Another discrete fibrous **bone** element formed of demineralized **cortical bone** fibers or powder, has a structure so as to fit into the channel. The elements are connected through a pin. DESCRIPTION - An INDEPENDENT CLAIM is included for fusion **implant** formation method

USE - For fusing adjacent vertebrae.

ADVANTAGE - The structure of bone elements simplifies the assembly process of the implant.

DESCRIPTION OF DRAWINGS - The figure shows an isometric view of the spinal implant.

10 Discrete **bone** element

26 Channel

32,34 Side surfaces

Original Abstracts: A C-shaped or ring shaped implant formed of cortical bone has its C-shaped or inner channel filled with a bone promoting material which is preferably demineralized bone fibers formed as a flexible wet sheet or may be cancellous bone, pressed bone fibers formed from demineralized cortical bone chips soaked in acid, or a flex material formed of demineralized bone growth promoting bone fibers... ... them to the outer bone. A filled bone ring may be sliced to form annular filled sections which are then divided into mirror image C-shaped halves each forming an implant. Flex material of compressed bone fibers may be formed with an opening shaped to receive a cortical bone implant element having a C-shaped channel. The flex material surrounds the cortical bone element and fills its channel. Other embodiments are disclosed... ... A C-shaped or ring shaped implant formed of cortical bone has its C-shaped or inner channel filled with a bone promoting material which is preferably demineralized bone fibers formed as a flexible wet sheet or may be cancellous bone, pressed bone fibers formed from demineralized cortical bone chips soaked in acid, or a flex material formed of demineralized bone growth promoting bone fibers. The discrete bone filler element... ... them to the outer bone. A filled bone ring may be sliced to form annular filled sections which are then divided into mirror image Cshaped halves each forming an implant. Flex material of compressed bone fibers may be formed with an opening shaped to receive a cortical bone implant element having a C-shaped channel. The flex material surrounds the cortical bone element and fills its channel. Other embodiments are disclosed. ...Claims: for promoting bone growth between said adjacent vertebrae, the second bone element having a shape that is complementary to said channel for forming an integral implant unit with said bone of the first type; andmeans for securing the first element to the second element...

18/25,K/11 (Item 11 from file: 350) Links
Fulltext available through: Order File History
Derwent WPIX
(c) 2009 Thomson Reuters. All rights reserved.

WPI Acc no: 2001-597807/200168

XRAM Acc no: C2001-176951 XRPX Acc No: N2001-445712

Cranium implant for use in brain surgery consists of a plate of spongy, cortical or compact bone material of human or animal origin preferably obtained by dehydration

Patent Assignee: KOSCHATZKY K (KOSC-I); LOWEL M (LOWE-I); TUTOGEN MEDICAL

GMBH (TUTO-N)

Inventor: KOSCHATZKY K; LOEWEL M; LOWEL M
Patent Family (5 patents, 93 & countries)

Patent Number	Kind	Date	Update	Type
DE 10014616	A1	20010927	200168	В
WO 2001072244	A1	20011004	200168	E
AU 200140557	A	20011008	200208	E
EP 1265554	A1	20021218	200301	E
US 20040059422	A1	20040325	200422	E

DE 10014616

Local Applications (no., kind, date): DE 10014616 A 20000324; WO 2001EP936 A 20010129; AU 200140557 A 20010129; EP 2001911548 A 20010129; WO 2001EP936 A 20010129; US 2002239619 A 20021126 Priority Applications (no., kind, date): DE 10014616 A 20000324

Alerting Abstract DE A1

NOVELTY - A cranium implant consists of a plate (1) of spongy, cortical or compact bone material of human or animal origin.

USE - None given.

DESCRIPTION OF DRAWINGS - The drawing shows a plate of bovine **bone compact** material with holes and curvature.

- 1 bovine bone compact material ;
- 2 holes ; and
- 3 curvature .

23/25,K/41 (Item 41 from file: 350) Links

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0014443876 & & Drawing available WPI Acc no: 2004-634586/200461 Related WPI Acc No: 1992-406998; 1992-407006; 1993-125932; 1993-404771; 1994-092210; 1994-233340; 1994-240674; 1994-293055; 1995-146667; 1995-350397; 1996-238619; 1996-383554; 1997-020009; 1997-099322; 1997-447852; 1997-469887; 1997-558017; 1998-040884; 1998-100214; 1998-144669; 1998-239066; 1998-593885; 1999-130313; 1999-243084; 1999-243093; 1999-443091; 1999-478165; 1999-539487; 2000-115843; 2000-170338; 2000-316553; 2000-429846; 2000-464731; 2000-524078; 2000-531963; 2000-664285; 2001-060243; 2001-111909; 2001-146195; 2001-158464; 2001-225865; 2001-256661; 2001-335217; 2001-373618; 2001-464368; 2001-496417; 2001-513534; 2001-541212; 2001-580208; 2001-625006; 2002-025562; 2002-315057; 2002-382134; 2002-403322; 2002-404343; 2002-413208; 2002-425326; 2002-433604; 2002-434608; 2002-507513; 2002-565627; 2002-589815; 2002-627058; 2002-635503; 2002-642396; 2002-664619; 2002-673585; 2002-706046; 2002-711855; 2002-749526; 2003-029812; 2003-057064; 2003-089999; 2003-220849; 2003-247723; 2003-276880; 2003-277284; 2003-278066; 2003-278067; 2003-415342; 2003-416704; 2003-456139; 2003-479353; 2003-540700; 2003-558800; 2003-568878; 2003-596701; 2003-687063;

```
2003-695887; 2003-720043; 2003-743415; 2003-747318; 2003-754600; 2003-778028; 2003-787950; 2003-874331; 2003-900689; 2004-060591; 2004-179103; 2004-280796; 2004-389208; 2004-389247; 2004-389274; 2004-487398; 2004-517208; 2004-517209; 2004-625134; 2004-651420; 2004-689912; 2005-010704; 2005-019512; 2005-029413; 2005-056915; 2005-466593; 2005-550885; 2005-618183; 2005-648883; 2005-796407; 2006-115457; 2006-170683; 2006-362313; 2006-567599; 2006-621350; 2006-716854; 2007-96978; 2007-006926; 2007-024680; 2007-025025; 2007-082278; 2007-324700; 2007-511983; 2007-569301; 2007-585308; 2007-891746; 2008-C35145; 2008-C62749; 2008-C75729; 2008-D00551; 2008-F48669; 2008-G01951; 2008-G50641; 2008-H10820; 2008-H54986; 2008-H70475; 2008-H88941; 2008-K90508 XRPX Acc No: N2004-501631
```

Body tissue e.g. bone, stabilizing implant for tissue shaping/compressing apparatus, has core partially formed of allograft material which expands by imbibing fluid, and expandable retainer partially enclosing core

Patent Assignee: BONUTTI P M (BONU-I)

Inventor: BONUTTI P M

Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Type
US 20040172140	A1	20040902	200461	В

US 20040172140

Local Applications (no., kind, date): US 1991728247 A 19910812; US 1994273028 A 19940708; US 1996590193 A 19960123; US 1997834028 A 19970411; US 1999263006 A 19990305; US 2000602743 A 20000623; US 2001798870 A 20010301; US 2002279451 A 20021024; US 2004793265 A 20040304

Priority Applications (no., kind, date): US 1991728247 A 19910812; US 1994273028 A 19940708; US 1996590193 A 19960123; US 1997834028 A 19970411; US 1999263006 A 19990305; US 2000602743 A 20000623; US 2001798870 A 20010301; US 2002279451 A 20021024; US 2004793265 A 20040304

Alerting Abstract US A1

NOVELTY - The **implant** has a core partially formed of a desiccated allo**graft** material which expands by imbibing **fluid**. An expandable retainer (330) is made of a polymeric material and partially encloses the core. The retainer includes a set of crossed filaments and a set of openings. The retainer imbibes body **fluid/water** from a host **tissue** (338) and creates a mechanical interlock.

USE - Used by a surgeon in a **tissue shaping/compressing** apparatus for stabilizing or **grafting** body **tissue** e.g. **bone** and ligament.

ADVANTAGE - The **implant** allows the **bone** or other **tissue** such as ligament to be re**shape**d while still leaving the **bone** in a whole condition and without substantial **tissue** damage. The use of living **tissue** in the **graft** promotes **bone** healing.

DESCRIPTION OF DRAWINGS - DESCRIPTION OF DRAWING - The drawing shows an expanding ${f tissue}$ retainer.

- 330 Expandable retainer
- 332 Graft tissue
- 334 **Tissue/bone** space
- 336 Edge
- 338 Host tissue

23/25,K/58 (Item 58 from file: 350) Links
Fulltext available through: Order File History
Derwent WPIX
(c) 2009 Thomson Reuters. All rights reserved.

0012903440 & & Drawing available WPI Acc no: 2002-122484/200216 XRPX Acc No: N2002-091867

Osteogenic implants derived from bone can be laminated or three-dimensionally shaped

Patent Assignee: **OSTEO**TECH INC (OSTE-N)
Inventor: BOYCE T M; KAES D; SCARBOROUGH N L
Patent Family (13 patents, 95 & countries)

Patent Number	Kind	Date	Update	Туре
WO 2002002156	A2	20020110	200216	В
US 20020035401	A1	20020321	200224	E
AU 200170153	A	20020114	200237	E
EP 1296726	A2	20030402	200325	E
KR 2003027934	А	20030407	200353	E
EP 1296726	B1	20040204	200410	E
JP 2004501719	W	20040122	200411	E
NZ 523867	А	20040227	200418	E
DE 60101967	E	20040311	200419	E
ES 2215913	Т3	20041016	200469	E
US 6808585	В2	20041026	200470	E
US 6863694	B1	20050308	200518	E
AU 2001270153	В2	20060706	200707	E

WO 2002002156

Local Applications (no., kind, date): WO 2001US20220 A 20010627; US 2000610026 A 20000703; US 2001973597 A 20011009; AU 200170153 A 20010627; EP 2001948706 A 20010627; WO 2001US20220 A 20010627; KR 2003700036 A 20030103; EP 2001948706 A 20010627; WO 2001US20220 A 20010627; WO 2001US20220 A 20010627; US 20010627; US 2001US20220 A 20010627; DE 60101967 A 20010627; EP 2001948706 A 20010627; WO 2001US20220 A 20010627; DE 60101967 A 20010627; US 2000610026 A 20000703; US 2001973597 A 20011009; US 2000610026 A 20000703; AU 2001270153 A 20010627 Priority Applications (no., kind, date): US 2000610026 A 20000703; US 2001973597 A 2001973597 A 20011009

Alerting Abstract WO A2

NOVELTY - The **osteoimplant** is made up of elongate **bone**-derived elements, preferably comprising 20 to 99 percent by weight, and **bone** powder. The **bone**-derived elements are mixed with a binder and then mechanically **shaped**. The **implant** can also be of laminated construction.

USE - Foe **osteo**genic **osteoimplants**, particularly in periodontal applications. ADVANTAGE - Can be **shape**d closely to the exterior of **bony** surfaces. Maintains its three-dimensional architecture even after **rehydration** and deformation prior to **implantation**. **Size** of **implant** is limited only by the total amount of starting material available and not by its **size** and **shape**. DESCRIPTION OF DRAWINGS - The diagram shows a perspective view of the assembly of a **bone**-derived laminate **implant** possessing layers of partially

assembly of a **bone**-derived laminate **implant** possessing layers of partially demineralized **shaped bone** material alternating with other layers of partially demineralized **shaped bone** material and/or optional materials.

Original Abstracts: making an osteogenic osteoimplant having not greater than about 32% void volume, the method comprising: providing a coherent mass of bone-derived particles; and, mechanically shaping the coherent mass of bone-derived particles to form an osteogenic osteoimplant in the form of a flexible sheet... ... making an osteogenic osteoimplant having not greater than about 32% void volume, the method comprising: providing a coherent mass

of bone-derived particles; and, mechanically shaping the coherent mass of bone-derived particles to form an osteogenic osteoimplant in the form of a flexible sheet... ... making an osteogenic osteoimplant having not greater than about 32% void volume, the method comprising: providing a coherent ${\it mass}$ of bone-derived particles; and, mechanically shaping the coherent mass of bone-derived particles to form an osteogenic osteoimplant in the form of a flexible sheet... ... making an osteogenic osteoimplant having not greater than about 32% void volume, the method comprising: providing a coherent mass of bone-derived particles; and, mechanically shaping the coherent mass of bone-derived particles to form an osteogenic osteoimplant in the form of a flexible sheet... ... making an osteogenic osteoimplant having not greater than about 32% void volume, the method comprising: providing a coherent mass of bone-derived particles; and, mechanically shaping the coherent mass of bone-derived particles to form an osteogenic osteoimplant in the form of a flexible **sheet...** ... Claims: or more biocompatible components, the coherent mass formed at least in part from elongate bone-derived elements optionally in combination with bone powder; and, mechanically shaping the coherent mass of bone particles to form the osteogenic osteoimplant...

23/25,K/60 (Item 60 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0012854507 & & Drawing available WPI Acc no: 2002-713216/200277 Related WPI Acc No: 1999-190433

XRPX Acc No: N2002-562738

Implant used for cervical vertebral fusion operation, has internal canal surrounded by circular, elliptical or asymmetrical-shaped continuous or discontinuous wall of cortical bone

Patent Assignee: CARTER K C (CART-I); DULEBOHN D H (DULE-I); GROOMS J M (GROO-I); SANDER T (SAND-I)

Inventor: CARTER K C; DULEBOHN D H; GROOMS J M; SANDER T

Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Type
US 20020138143	A1	20020926	200277	В

US 20020138143

Local Applications (no., kind, date): US 1997920630 A 19970827; US 1998701933 A 19980528; US 2001905683 A 20010716

Priority Applications (no., kind, date): US 1997920630 A 19970827; US 1998701933 A 19980528; US 2001905683 A 20010716

Alerting Abstract US A1

NOVELTY - An internal canal (104) is surrounded by a circular, elliptical or asymmetrical-shaped continuous or discontinuous wall of cortical bone.

DESCRIPTION - INDEPENDENT CLAIMS are also for the following:

a method for **manufactur**ing an **implant**; a broach for **forming** a desired **shape** canal; and an apparatus for **forming** a **bone plug**.

USE - Used for cervical vertebral fusion operation in human and animals. ADVANTAGE - Allows monitoring of fusion **implant** stability and reliability. Enables to optimize retention of the **implant** within the cervical spine after

proper placement.
DESCRIPTION OF DRAWINGS - The figure shows a fusion implant.
104 Internal canal

Original Abstracts: fusion procedures. The implant is derived from allograft or autograft cortical bone sources, is machined to form a symmetrically or asymmetrically shaped (e.g. a substantially "D"-shaped) implant having a canal running therethrough according to methods of this invention, and inserted into the space between adjacent cervical vertebrae to provide support and induce fusion of the adjacent vertebrae. Osteogenic, osteoinductive or osteoconductive materials may be packed into the canal of the implant to expedite vertebral fusion and to allow autologous bony ingrowth. ...Claims:implant comprising a canal surrounded by a continuous or discontinuous wall of cortical bone in the shape of a circle, an ellipse, or an asymmetric shape, thereby forming an implant having a top face and a bottom face, each of which is substantially planar, with said planes being substantially parallel to each other.

23/25,K/64 (Item 64 from file: 350) <u>Links</u>

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0012386165

WPI Acc no: 2002-329629/200236

XRAM Acc no: C2002-095233

Dehydrating monolithic bone, useful for implantation repair of bones, comprises treatment with dehydrating liquid, dehydration without lyophilization and packaging

Patent Assignee: OSTEOTECH INC (OSTE-N)

Inventor: BOYCE T M

Patent Family (5 patents, 95 & countries)

Patent Number	Kind	Date	Update	Туре
WO 2002015688	A2	20020228	200236	В
AU 200188411	A	20020304	200247	E
KR 2003036706	A	20030509	200358	E
EP 1359949	A2	20031112	200377	E
JP 2004506660	W	20040304	200417	E

WO 2002015688

Local Applications (no., kind, date): WO 2001US26603 A 20010824; AU 200188411 A 20010824; KR 2003702390 A 20030218; EP 2001968138 A 20010824; WO 2001US26603 A 20010824; WO 2001US26603 A 20010824; JP 2002520615 A 20010824 Priority Applications (no., kind, date): US 2000644614 A 20000824

Alerting Abstract WO A2

NOVELTY - Method for **dehydrat**ing a monolithic **bone** (A), intended for **implant**ation, which conserves its biomechanical properties during **dehydrat**ion, **pack**aging and storage, comprises:

treating (A) with at least one dehydrating liquid (I);
dehydration without lyophilization; and
packaging treated (A).

DESCRIPTION - INDEPENDENT CLAIMS are also included for:

A method for dehydrating (A) which comprises:
contacting the bone with at least one biocompatible dehydrating liquid;
removing the dehydrating liquid; and
packaging the dehydrated bone; and
Use of (A) for repair of bone comprises:
exposing a surgical site;
implanting the bone in the surgical site; and
closing the surgical site.

USE - After rehydration (A) is implanted for repair of a wide range of bones, e.g. to treat fractures or non-unions or to induce arthrodeses.

ADVANTAGE - Dehydration with (I) produces a tougher product than freezedrying and smaller dimensional changes, with better retention of mechanical properties (reduced risk of fracture during implantation). The dehydrated bone can be stored for up to 5 years without excessive loss of strength.

Original Abstracts: A method for dehydrating a monolithic bone intended for implantation is provided. The method serves to conserve at least one of the biomechanical properties of the bone during the dehydration of the bone and its subsequent packaging. Also provided..... A method for dehydrating a monolithic bone intended for implantation is provided. The method serves to conserve at least one of the biomechanical properties of the bone during the dehydration of the bone and its subsequent packaging. Also provided is a monolithic bone for implantation and a method of using the bone for the repair of damaged bone...

23/25,K/71 (Item 71 from file: 350) <u>Links</u>
Fulltext available through: <u>Order File History</u>
Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0010956617 & & Drawing available WPI Acc no: 2001-579737/200165

Related WPI Acc No: 1998-582418; 1999-633378; 2002-371085

XRPX Acc No: N2001-431559

Composite allograft for orthopedic surgery has cancellous bone chips that are molded and compressed with bone cement to preset shape having smooth inner surface and irregular outer surface

Patent Assignee: UNIV ARKANSAS (UYAR-N)

Inventor: FLAHIFF C; HOGUE W; HOLLIS J M; NELSON C

Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Туре
US 6293971	B1	20010925	200165	В

US 6293971

Local Applications (no., kind, date): US 1996647424 A 19960311; US 1998121938 A 19980724; US 1999343135 A 19990629

Priority Applications (no., kind, date): US 1996647424 A 19960311; US 1998121938 A 19980724; US 1999343135 A 19990629

Alerting Abstract US B1

NOVELTY - Cancellous bone chips (73) are molded and compressed with bone cement to a predetermined shape having a smooth inner surface (72) consisting

essentially of **harden**ed **bone** cement and an irregular outer surface (71) consisting essentially of exposed **cancellous bone** chips.

USE - For orthopedic surgery e.g. hip replacement surgery.

ADVANTAGE - Provides strong inner surface made of **harden**ed cement material. DESCRIPTION OF DRAWINGS - The figure is the sectional elevational view of a synthetic composite acetabular cup.

- 71 Outer surface
- 72 Inner surface
- 73 Cancellous bone chip

Original Abstracts: A composite allograft press comprises a loading frame and a two piece mold to form an composite allograft and in particular an acetabular cup from impacted cancellous bone chips and cement. Pressure is applied by a manually operated lever through a rack-and....mechanism to a plunger attached to one part of the mold. Compression load switches in-line with the plunger indicate the correct loading to the mold to produce a composite allograft in which the inner surface is smooth and comprised essentially of hardened bone cement material. The outer portion of the allograft may have limited cement... Claims: A composite allograft, comprising: cancellous bone chips molded and compressed with bone cement to a predetermined shape having an inner surface and an outer surface; said inner surface consisting essentially of hardened bone cement wherein...

23/25,K/81 (Item 81 from file: 350) **Links**

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0010104471 & & Drawing available WPI Acc no: 2000-411585/200035

XRAM Acc no: C2000-124609 XRPX Acc No: N2000-307732

Bone plug for blocking of canal in bone has radially expandable body of specified height, which is larger than its average wall thickness

Patent Assignee: SPIERINGS P T J (SPIE-I)

Inventor: SPIERINGS P T J

Patent Family (6 patents, 88 & countries)

Patent Number	Kind	Date	Update	Туре
WO 2000028926	A1	20000525	200035	В
NL 1010539	C2	20000515	200036	E
AU 200012969	A	20000605	200042	E
EP 1128788	A1	20010905	200151	E
JP 2002529195	W	20020910	200274	E
US 6669733	B1	20031230	200402	E

WO 2000028926

Local Applications (no., kind, date): WO 1999NL695 A 19991112; NL 1010539 A 19981112; AU 200012969 A 19991112; EP 1999956343 A 19991112; WO 1999NL695 A 19991112; WO 1999NL695 A 19991112; US 2001831718 A 20010718

Priority Applications (no., kind, date): NL 1010539 A 19981112

Alerting Abstract WO Al

NOVELTY - A bone plug has an at least nearly solid body that is radially

expandable. The height of the body is at most 8 times the average wall thickness of the body.

DESCRIPTION - A **bone plug** has an at least nearly solid body which expands radially at axial **compress**ion. It has two locking elements which can be fixed on various distances to each other, in between which the body with its axial boundaries is positioned. The first locking element (67) comprises a stem (71) which is provided with radial protrusions (73) which are positioned next to each other in an axial direction on the stem. The stem protrudes through an axial opening of the body. The second locking element is positioned around the stem and can lock behind the protrusions. The height of the body is at most 8 times the average wall thickness of the body.

USE - The **bone plug** is used in the medical field for permanent or temporarily **block**ing of a canal in a **bone**. The **bone plug** is especially suited for **block**ing of unround canals, like the canal of the fermoral **bone** which has an oval-**shape**d cross-section with an irregular surface of the endosteal wall. ADVANTAGE - The radial protrusions are located near to each other in the longitudinal direction of the stem, making **compress**ion of the body possible in smaller steps than with the known **bone plug**, where the protrusions are positioned on a large distance to each other. By this possibility of accurate control of the amount of **compression** of the body, the **bone plug** can better be installed in a canal and a canal can better be **block**ed than with the known **bone plug**.

DESCRIPTION OF DRAWINGS - The figure shows a longitudinal section of the **bone plug** fixed in an instrument in the **compress**ed condition.

- 67 First locking element
- 71 Stem
- 73 Protrusions
- 77 Interrupted ring
- 79 Annular **shape**d plate

Bone plug for blocking of canal in bone has radially expandable body of specified height, which is larger than its average wall thickness ...Original Titles: BONE PLUG Bone plug BONE PLUG Alerting Abstract ... known bone plug, where the protrusions are positioned on a large distance to each other. By this possibility of accurate control of the amount of compression of the body, the bone plug can better be installed in a canal and a canal can better be **block**ed than with the known **bone plug...** Original Publication Data by AuthorityArgentinaPublication No. ...Original Abstracts:65) axially locked the bone plug comprises a first locking element (67) which is formed by a disc (69) with attached to it a stem (71) provided with saw tooth shaped protrusions (73) which protrudes through an axial opening in the body (65) and a second locking element (75) which is formed by an interrupted ring... \dots one of the protrusions (73) and the annular plate (79) is positioned between the interrupted ring (77) and the body (65). Fixating of the bone plug (61) in **the** canal is carried out by pushing the interrupted ring (77) along the stem (71) until it locks behind one of the protrusions (73), whereby the...

23/25,K/83 (Item 83 from file: 350) Links
Fulltext available through: Order File History
Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0009736557

WPI Acc no: 2000-021962/200002 XRAM Acc no: C2000-005241 XRPX Acc No: N2000-016236

Producing a cleaned cut bone graft by centrifugation for transplanting into humans

Patent Assignee: LIFE NET RES FOUND (LIFE-N)

Inventor: FORD L; WOLFINBARGER L

Patent Family (1 patents, 1 & countries)

Patent Number	Kind	Date	Update	Туре
US 5977432	A	19991102	200002	В

US 5977432

Local Applications (no., kind, date): US 1997871601 A 19970609 Priority Applications (no., kind, date): US 1997871601 A 19970609

Alerting Abstract US A

NOVELTY - **Produc**ing a cleaned cut **bone graft** for **transplant**ation into humans comprises centrifuging a cut **bone graft** to remove the **bone** marrow from **cancellous bone** spaces.

DESCRIPTION - INDEPENDENT CLAIMS are also included for:

cleaning a cut **bone graft** comprising selecting an intact **bone**, cutting it into one or more **graft**s, and centrifuging as above; and the **bone graft**s **produc**ed by the above methods.

USE - The **grafts** are used for clinical applications such as **transplant**ing cadaveric **bones**, and large **bones** from other species into humans.

ADVANTAGE - The cleaning procedure effectively removes substantially all of the **bone** marrow elements effectively removing cells capable of harboring HIV which are abundant in **bone** marrow with minimal handling and **process**ing, thus **reduc**ing the risk of viral, bacterial and fungal transmission. High pressure **washing** or exposure of the **graft** to negative **atmospheric** pressure is prevented. The **solvents** comprising a combination of solutes improves solvent penetrability into the **bone graft** and intensifies cavitation induced by ultrasonics. Alcohols and detergent solutions enhance solubility of **bone** marrow, **reduc**e surface tension of aqueous solutions and inactivate virus and bacteria. Cadaveric **bones** are thus **process**ed into clinically usable **bone grafts**.

Technology Focus ...subjected to sonic washing with a washing solution (A), incubated by soaking for >= 6 hours and further washed with washing (II). After washing with a washing solution (II), the bone graft is incubated in a solution comprising water and subjected to another centrifugation resulting in a cleaned bone graft essentially free from bone marrow. Prior to... Extension Abstract ...the container. The femur head was placed in a sterile container. The container was sealed and placed into the centrifuge. The grafts were centrifuged for 3 minutes to dry and remove any remaining water.

23/25,K/97 (Item 97 from file: 350) <u>Links</u>

Fulltext available through: Order File History

Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0006687200 & & Drawing available WPI Acc no: 1994-067102/199409 XRAM Acc no: C1994-030063

XRPX Acc No: N1994-052529

Sterilising bone transplant material - using sealed vessel filled with sterile fluid for heating to given temp. and holding before cooling and freezing

Patent Assignee: TULASZEWSKI O (TULA-I); TULASZOWSKI O (TULA-I)

Inventor: KNAEPLER H; KNAEPLER H P D; VON GARREL T

Patent Family (12 patents, 21 & countries)

Patent Number	Kind	Date	Update	Type
EP 584484	A1	19940302	199409	В
DE 4227830	C1	19940331	199412	E
CA 2104498	A	19940222	199419	E
TW 233267	A	19941101	199503	E
US 5429810	A	19950704	199532	E
JP 2506553	В2	19960612	199628	E
JP 7023993	A	19950127	199631	E
US 5591398	A	19970107	199708	E
CA 2104498	С	19990119	199914	E
KR 199701492	В1	19970211	199933	E
EP 584484	В1	19991013	199947	E
DE 59309831	G	19991118	200001	E

EP 584484

Local Applications (no., kind, date): EP 1993109964 A 19930622; DE 4227830 A 19920821; CA 2104498 A 19930820; TW 1993106786 A 19930823; US 1993109347 A 19930820; JP 1993200711 A 19930812; JP 1993200711 A 19930812; US 1993109347 A 19930820; US 1995418630 A 19950407; CA 2104498 A 19930820; KR 199315205 A 19930805; EP 1993109964 A 19930622; DE 59309831 A 19930622; EP 1993109964 A 19930622

Priority Applications (no., kind, date): DE 4227830 A 19920821

Alerting Abstract EP A1

To disinfect bone transplant material, the transplant (18) is prepd. and measured, and inserted into a vessel (13) of a known capacity. The vessel (13) is filled with a sterile fluid up to a vessel wall marking over the material (18), and the vessel is closed with a self-sealing cover (26) with a penetration zone (28). The closed vessel (13) is inserted into a heater (1) and heated over a constant initial time span to a final temp. and it is held at this temp. for a further time span according to the dimensions of the transplant material (18). The vessel (13) is then allowed to cool to room temp. The penetration zone (28) of the cover (26) is punctured, and a transfer set also punctures the cover of a catch vessel, for the fluid to be transferred from the vessel (13) to a catch container. The transfer set is removed, and the vessel (13) is placed in a cool zone to freeze the transplant material (18).

USE/ADVANTAGE - The technique is for the prepn. and sterilisation of **bone transplant** material, esp. human **spongi**ose **transplant**ation material. The sterilisation is simple and rapid, and can be effected in the operating theatre, without further **process**ing and free of contamination, in a costeffective action.

Equivalent Alerting Abstract ...Appts. for sterilising a bone graft, e.g. a human spongiosa bone graft, comprises (a) a housing having an upper surface contg. open-topped heating and cooling recesses; (b) a first container for receiving a bone graft; (c... Technology Focus Original Publication Data by AuthorityArgentinaPublication No. ...Original Abstracts:An apparatus for sterilizing bone grafts, such as human spongiosa grafts, includes a container

for receiving the bone graft together with a quantity of sterile liquid sufficient to cover the bone graft. A penetrable self-sealing closure member is provided for closing the container, whereupon the container is initially heated at a given sterilizing temperature for a constant first period of time, and is subsequently heated for a variable second period of time, the duration of which is a function of the size of the bone graft. The container is then cooled to room temperature, and a transfer tube arrangement inserted at one end through the closure member to transfer the liquid within the... ... A method and apparatus for sterilizing bone grafts, wherein the bone graft together with a quantity of sterile liquid sufficient to cover the bone graft is initially heated at a given sterilizing temperature for a constant first period of time, and is subsequently heated for a variable second period of time the duration of which is a function of the size of the bone graft. The bone graft is then cooled to room temperature, and the liquid transferred to a container. The sterilized bone graft is frozen, and the liquid in the container is analyzed for infectious... ... Claims: 1. Method of sterilizing bone grafts, especially human spongiosa grafts, comprising the following steps:

- a) providing the bone graft (18) and evaluating its size,
- b) placing the **bone graft** (18) in a vessel (13) of..... **heat**ing apparatus (1) and **heat**ing the vessel (13) for a constant first period of time to a final temperature and maintaining this final temperature for **a** second period **of time** which is fixedly related to the measured **size** of the **bone graft** (18), f) cooling the vessel (13) to room temperature,
- g) penetrating the penetrationthe transfer set (33) from the vessel lid and introducing the vessel (13) into a cooling chamber in order to ${\bf freez}$ e the bone graft (18). Apparatus for sterilizing a bone graft, such as a human spongiosa bone graft, comprising: (a) a housing (1) having an upper surface (2) containing open-topped heating (3) and cooling (4) recesses; (b) a first container (13) receiving a bone graft (18), said heating and cooling recesses each being of a size to receive at least the bottom portion of said container when said container has a first vertical... ... bone graft; (c) closure means (26) for closing said container opening, said closure means being of the penetrable self-sealing type and including: (1) a first screw cap (26) threadably connected with said container, said screw cap containing a central opening; and (2) an internal annular protective wall portion (31) arranged concentrically about said central opening and extending in the direction of said bottom wall, said internal annular protective wall portion being operable to support the bone graft when said first container is in an inverted second vertical orientation... produce a sterilization temperature for a constant first period of time (T1) when at least the bottom portion of said container is seated in said heating recess; (e) a memory (M); (f) means (15) for inputting to said memory the measured ${\bf size}$ (S) of the ${\bf bone}$ graft; . (q) means (9) connected with said memory for container when said first container is in an inverted second verticle orientation; and (j) screen means (25) arranged within said first container for normally supporting the bone graft in spaced relation above said bottom wall when said first container is in said first vertical orientation... ... to cover said bone graft and to reach a predetermined level (24) in the container; (d) closing said container with a penetrable self-sealing closure member (26);(e) heating the container at a given temperature for a predetermined first period of time, whereby the temperature of the sterile liquid approaches a preselected sterilizing temperature

Advanced Search

1. Database

Select patent database:	Worldwide	teast Sec
	•	
2. Search terms		•
Enter keywords in English		
Keyword(s) in title:		plastic and bicycle
Keyword(s) in title or abstract:	prepar* bone demineral*	hair
Publication number:		WO03075629
Application number:		DE19971031696
Priority number:		WO1995US15925
Publication date:		yyyymmdd
Applicant(s):		Institut Pasteur
Inventor(s):		Smith
European Classification (ECLA):		F03G7/10
International Patent Classification (IPC):	a61	H03M1/12
\$75 615 185 185	SEARCH CLEAR	

METHOD FOR PREPARING BONE TRANSPLANTER

Publication number: KR20020011164 (A)

Publication date:

2002-02-08

Inventor(s):

EOM IN UNG [KR]

Applicant(s):

HUMAN TISSUE ENGINEERING CT CO [KR]

Classification:

- international:

A61L27/38; A61L27/00; (IPC1-7): A61L27/38

- European:

Application number: KR20000044494 20000801 Priority number(s): KR20000044494 20000801

Abstract of KR 20020011164 (A)

PURPOSE: A method for preparing bone transplanter is provided to obtain an excellent bone transplantation effect without occurring an inflammation and an immune rejection reaction after transplanting. CONSTITUTION: In the method for preparing bone transplanter, allogenic bone is collected, and soft tissue is removed from the bone. The bone is pulverized, washed, and classified into bone pieces and bone powders. The split bone pieces or bone powders are washed and defatted using ethanol and ether, respectively. The bone is dried at room temperature, and demineralized using hydrochloric acid. The demineralized bone is washed with saline solution or phosphate buffered saline, and further washed with ethanol and ether. The washed bone is dried at room temperature and lyophilized. The lyophilized bone is further classified by sizes to obtain bone transplanter.

Data supplied from the **esp@cenet** database — Worldwide

Also published as:

Cited documents:

US2347567 (A)

US3126884 (A)

US3127317 (A)

US3573082 (A)

DE2917135 (A1)

JP55045668 (A)

Artificial bonelike graft and method for producing the same

Publication number: US4277238 (A)

Publication date:

1981-07-07

Inventor(s):

KATAGIRI MASATAKA

Applicant(s):

KATAGIRI MASATAKA

Classification:

- international:

A61L17/00; A61C8/00; A61K6/00; A61K35/32; A61K38/17;


A61L27/00; A61L27/36; A61L17/00; A61C8/00; A61K6/00;


A61K35/32; A61K38/17; A61L27/00; (IPC1-7): A01N35/02

- European:

A61C8/00E; A61L27/36

Application number: US19790025730 19790330 Priority number(s): JP19780120618 19780928







Abstract of US 4277238 (A)

An artificial bonelike graft is disclosed. The graft of this invention comprises a biological material such as a bone piece and tooth taken from an animal or a human, which material is decalcified and defatted. Upon implanting the graft, it will be assimilated with the existing tissues and become a part of the living organs. A method for producing such grafts is also disclosed.







Data supplied from the **esp@cenet** database — Worldwide

LIST OF CITING DOCUMENTS

Approximately 20 document citing US4277238 (A)

1 Process for manufacturing a bone implant

Inventor: TOPOR BORIS PROF DR HABIL MED Applicant: JAKOB KARL [DE]; TOPOR BORIS

[MD] PROF DR HABIL MED [MD] (+1)

IPC: A61L27/36; A61F2/28; A61L27/00; (+3)

Publication info: EP1380312 (A1) — 2004-01-14

2 Multi-step process for making a bone regeneration paste

Inventor: TOPOR BORIS PROF DR HABIL MED Applicant: JAKOB KARL DIPL ING DR H C [DE]; [MD] TOPOR BORIS PROF DR HABIL MED [MD] (+1)

EC: A61L27/36

EC: A61L27/36

IPC: A61L27/36; A61F2/28; A61L27/00; (+2)

Publication info: EP1380311 (A1) — 2004-01-14

METHOD FOR REMOVAL OF WATER ASSOCIATED WITH

BONE WHILE DIMINISHING THE DIMENSIONAL CHANGES ASSOCIATED WITH LYOPHILIZATION

Inventor: BOYCE TODD M

Applicant: OSTEOTECH INC [US]

EC: A61F2/28; A61F2/46G; (+1)

IPC: A01N1/02; A61F2/28; A61F2/46; (+12)

Publication info: WO0215688 (A2) - 2002-02-28

4 METHOD OF TREATING AND DEHYDRATING BONE FOR

IMPLANTATION AND RESULTING BONE

Inventor: BOYCE TODD M; SHIMP LAWRENCE Applicant: OSTEOTECH INC [US]

Α

EC: A61F2/28; A61F2/46G; (+1)

IPC: A61F2/28; A61F2/46; A61L27/36; (+8)

Publication info: WO0215948 (A2) - 2002-02-28

5 Bone graft delivery surgical instruments

Inventor: SMITH MARGARET E [US]; CUSICK Applicant: HOWMEDICA OSTEONICS CORP

MICHAEL J [US] ec: A61F2/46A

IPC: A61B17/56; A61F2/46; A61M5/315; (+13)

Publication info: US6142998 (A) — 2000-11-07

Tooth implant and method for implantation

Inventor: FILHO NEY DE SOUZA BLAZZIO [BR] Applicant: FILHO, NEY DE SOUZA BLAZZIO

EC: A61B17/16H; A61C8/00; (+1)

IPC: A61B17/16; A61C8/00; A61F2/00; (+8)

Publication info: US6089867 (A) — 2000-07-18

Method and apparatus for implantation

Inventor: JONES SHEDRICK D [US]

Applicant: JONES, SHEDRICK D

EC: A61C8/00; A61C8/00F2; (+1)

IPC: A61C8/00; A61F2/46; A61C8/00; (+2)

Publication info: US6135772 (A) — 2000-10-24

Organic dental repair material for fillings etc. for human

teeth

Inventor: METZNER KLAUS [DE]

Applicant: METZNER KLAUS [DE]

EC: A61K6/02

IPC: A61K6/02; A61K6/02; (IPC1-7): A61K6/02;

(+1)

Publication info: DE4415671 (A1) - 1995-11-16

Visualization system for retrieval, identification, and

9 positioning of biological samples for subsequent

microscopic examination

Inventor: CAMIENER GERALD W [US]

Applicant: CAMIENER GERALD W [US]

EC: G01N1/30

IPC: G01N1/30; G01N1/30; (IPC1-7): G01N1/30;

(+1)

Publication info: US5290706 (A) - 1994-03-01

10 Method and means for fixing a joint prosthesis.

Inventor: BRUCE INGRID [SE]; BRUCE LARS Applicant: IDEA AB [SE]

[SE]

EC: A61F2/46A; A61F2/30B1; (+2)

IPC: A61F2/30; A61F2/36; A61F2/46; (+10)

Publication info: EP0501595 (A1) — 1992-09-02

PROTEIN COMPOSITION INDUCING A BINDING BETWEEN PARTS OF MINERALIZED TISSUE

Inventor: HAMMARSTROEM LARS [SE];

Applicant: BIOVENTURES NV [NL]

BLOMLOEF LEIF [SE] (+1)

EC: A61K6/00B; A61K35/32; (+1)

IPC: A61K38/00; A61K6/00; A61K35/32; (+10)

Publication info: US5098891 (A) - 1992-03-24

12 Biologic absorbable implant material for filling and closing

soft tissue cavities and method of its preparation

Inventor: REDL HEINZ [AT]; SCHLAG GUENTHER [AT] (+1)

Applicant: IMMUNO AG [AT]

EC: A61L24/00F; A61L24/10A; (+1)

IPC: A61L24/00; A61L24/10; A61L27/36; (+3)

Publication info: US5139527 (A) - 1992-08-18

13 Bone allograft material and method

Inventor: SIRES BRYAN S [US]

Applicant: UNIV NORTHWESTERN [US]

EC: A61F2/28: A61L27/36

IPC: A61F2/28; A61L27/36; A61F2/00; (+8)

Publication info: US5112354 (A) — 1992-05-12

Process for disinfecting musculoskeletal tissue and tissues

prepared thereby

Inventor: O'LEARY ROBERT K [US]

Applicant: OSTEOTECH INC [US]

EC: A61K31/00; A61K31/045; (+2)

IPC: A61K31/00; A61K31/045; A61L2/00; (+6)

Publication info: US5298222 (A) — 1994-03-29

15 Stents for bone augmentation by surgical implant

Inventor: BARRETT GARRET D [US]

Applicant: BARRETT GARRET D

EC: A61C8/00; A61F2/28; (+2)

IPC: A61C8/00; A61F2/28; A61F2/30; (+6)

Publication info: US4684370 (A) - 1987-08-04

Data supplied from the esp@cenet database — Worldwide

METHOD OF TREATING AND DEHYDRATING BONE FOR IMPLANTATION AND RESULTING BONE

Publication number:	WO0215948 (A2)		Also published as:
Publication date:	2002-02-28		WO0215948 (A3)
Inventor(s):	BOYCE TODD M; SHIMP LAWRENCE A	_	WO0215948 (A9)
Applicant(s):	OSTEOTECH INC [US]	Ē	AU8675501 (A)
Classification:			CA2420113 (A1)
- international:	A61F2/28; A61F2/46; A61L27/36; A61F2/00; A61F2/30; A61F2/28; A61F2/46; A61L27/00 ; A61F2/00; A61F2/30; (IPC1-		, ,
	7): A61L27/00		Cited documents:
	A61F2/28; A61F2/46G; A61L27/36 WO2001US26553 20010824 US20000644521 20000824		WO9519797 (A1) US6162258 (A) US4277238 (A) WO9951170 (A1) WO9966967 (A1)
			more >>

Abstract of WO 0215948 (A2)

Monolithic bone intended for implantation is treated in oder to conserve its mechanical strength during dehydration and subsequent packaging and to maintain the strength of the bone during the storage period preceding the rehydration and implantation of the bone. The method of treatment comprises contacting the bone with a mechanical strength-conserving amount of at least one biocompatible mechanical strength-conserving agent, the agent being a liquid organic material which is capable of penetrating and remaining in the bone during its dehydration, packaging and storage, dehydrating the bone containing the mechanical strength-conserving agent and packaging the dehydrated bone.

Data supplied from the esp@cenet database — Worldwide